

# OWL SERIES LED OUTDOOR Billboard Sign Light



<b>Project:</b>	
<b>Type:</b>	
<b>Catalog#:</b>	

## STANDARD



This billboard unit provides high light levels with even distribution, for spot lighting. The unit is weather resistant and suitable for most outdoor applications.

### Construction:

- Housing is made of heavy gauge extruded aluminum with die cast end plates and splice box fittings. Housing interior is finished in a baked enamel finish for maximum reflectivity and durability. Splice box is threaded for 3/4" conduit and contains adjusting screws for housing. Lens is clear smooth slide-on acrylic that resists yellowing.

### Electrical

All units are furnished with UL Listed Class P thermally protected ballast. Other voltages are available upon request. Fixtures meet requirements for UL Luminaire Standard # 1598. All units comply with National Energy Standard. All units are UL certified damp and wet location

### Mounting


Units are designed to be conduit mounted either individually, tandem, or in a continuous run



### WARRANTY & LISTINGS

- 5-year warranty of all electronics and housing.
- UL Certified for damp location

### DIMENSIONS



### Fixture Length

# of Lamps	T5HO	Length
1 or 2	F54T5HO	53"
<b>TANDEM</b>		
Single or Double	F54T5HO	101"

For Tandem Units Multiply Unit above by 2

max weight= 11lbs/53" 15lbs/101"

### Ordering Guide

Series	Size	Lumens	Color	Options																				
OD-LED	4 = 4FT 6 = 6FT 8 = 8FT	<table border="1"> <tr> <th>4FT</th> <th>8FT</th> </tr> <tr> <td>3220 (17W)</td> <td>3220 (17W)</td> </tr> <tr> <td>4480 (24W)</td> <td>4480 (24W)</td> </tr> <tr> <td>5705 (30W)</td> <td>5705 (30W)</td> </tr> <tr> <td>6910 (37W)</td> <td>6910 (37W)</td> </tr> <tr> <td>8640 (48W)</td> <td>8640 (48W)</td> </tr> <tr> <td>11797 (70W)</td> <td>11797 (70W)</td> </tr> <tr> <td></td> <td>13820 (74W)</td> </tr> <tr> <td></td> <td>17280 (96W)</td> </tr> <tr> <td></td> <td>23594 (140W)</td> </tr> </table>	4FT	8FT	3220 (17W)	3220 (17W)	4480 (24W)	4480 (24W)	5705 (30W)	5705 (30W)	6910 (37W)	6910 (37W)	8640 (48W)	8640 (48W)	11797 (70W)	11797 (70W)		13820 (74W)		17280 (96W)		23594 (140W)	3K 35K 4K 5K	EMB = emergency ballast FR = Frosted lens over LED Boards
4FT	8FT																							
3220 (17W)	3220 (17W)																							
4480 (24W)	4480 (24W)																							
5705 (30W)	5705 (30W)																							
6910 (37W)	6910 (37W)																							
8640 (48W)	8640 (48W)																							
11797 (70W)	11797 (70W)																							
	13820 (74W)																							
	17280 (96W)																							
	23594 (140W)																							

\*Call Factory for lumen options of 6FT models