

Project:	
Type:	
Catalog #:	

Features

Sizes	2x2 and 2x4
Finish	Pure White Satin
Diffuser	Anti-UV Frosted Polycarbonate Lens
Rated Life	75000 hours
Warranty	7 years

Construction

Manufactured for weather-proof durability using heavy duty die cast aluminum housing with anti-UV polyester coating to resist corrosion, discoloration, and scratching.

Applications

Primary use as 2x2 and 2x4 luminaires for ambient lighting of interior commercial spaces. Intended to provide ambient lighting in settings such as office spaces, schools, retail stores, and other commercial environments.

Listings

DLC Premium listed. UL certified to meet US and Canadian standards. FCC, CE and RoHS compliant. View DLC Premium listing at: designlights.org/qpl

Warranty

7 year exclusive limited warranty.



Performance

Wattage	See ordering information.
Voltage	120-277V
Frequency	50/60 Hz
Efficacy	140 lm/W
CCT	4000K or 5000K
CRI	≥ 80
Power Factor	≥ 0.9
THD	≤ 20%
Operating Temp.	-20°C to 40°C (-4°F to 104°F)
Dimming	0-10V * Dims to 1%

ORDERING INFORMATION

Model No.	Size	Wattage (W)	Voltage (V)	CCT (K)	Light Output	Efficacy (lm/w)	Rated Life
BLP7-22-3-4K	2x2	30	120-277V	4000K	4200 lm	140 lm/W	75000 hrs
BLP7-22-3-5K	2x2	30	120-277V	5000K	4200 lm	140 lm/W	75000 hrs
BLP7-24-38-4K	2x4	38	120-277V	4000K	5320 lm	140 lm/W	75000 hrs
BLP7-24-38-5K	2x4	38	120-277V	5000K	5320 lm	140 lm/W	75000 hrs
BLP7-24-50-4K	2x4	50	120-277V	4000K	7000 lm	140 lm/W	75000 hrs
BLP7-24-50-5K	2x4	50	120-277V	5000K	7000 lm	140 lm/W	75000 hrs
BLP7-24-72-4K	2x4	72	120-277V	4000K	10080 lm	140 lm/W	75000 hrs
BLP7-24-72-5K	2x4	72	120-277V	5000K	10080 lm	140 lm/W	75000 hrs