

Project:	
Type:	
Catalog #:	



## HOUSING

- Durable, die-cast aluminum housing with heat dissipating fins
- White, dark bronze, or black polyester powder-coat finish

## LEDs

- LM-80 certified high performance and reliable LEDs

## ELECTRICAL

- Universal 120-277VAC or 347-480VAC input voltage
- 1-10V dimming optional

## MOUNTING

- Pendant or surface mount

## LISTINGS

- Wet location
- IP65 rated fixture


## RECOMMENDED USE

- Retail and grocery
- Parking Structures
- Walkways



## PHOTOMETRICS

Parking Garage



## ACCESSORIES



### Sensor - Screw on, 120V-277V

**USE:** Sensor can be pre-installed in factory or field installed



### Emergency Box

NO. EB-8W/90min-1  
**USE:** 900lm 90min.

**Housing**  
One piece die cast housing better waterproofing, suitable for both indoor and outdoor application.

**Mounting Bracket**  
Suitable for J-BOX mounting, and easy for installation, also support pendant mounting, wires coming out from the back for easier wire connections.

**PHOTOMETRY**  
Parking Garage Photometry and polycarbonate optical lens with heat resisting.

**1/2inch knock hole**  
Support wires coming from the hole for easier wire connections. Optional PIRsensor and Emergency Battery.




## PERFORMANCE DATA

			4000K(70CRI)		5000K(70CRI)	
SYSTEM WATTS	PHOTOMETRY	VOLTAGE	LUMENS	LPW	LUMENS	LPW
20W	Parking Garage	120-277VAC	2600lm	130lm/W	2600lm	130lm/W
27W	Parking Garage	120-277VAC	3750lm	139lm/W	3800lm	141lm/W
40W	Parking Garage	120-277VAC/347-480V	5350lm	134lm/W	5450lm	136lm/W
60W	Parking Garage	120-277VAC/347-480V	7800lm	133lm/W	8000lm	133lm/W




## DIMENSION

unit: inch/mm

Net Weight:  
20W: 3.536lbs  
27W: 3.615lbs  
40W: 4.166lbs



Net Weight:  
60W: 5.070lbs



## ORDERING GUIDE

Fixture Type	Wattage	Input Voltage	CCT	Finish	Sensor (Option)	Dimmable (Option)	Emergency Battery (Option)
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
CPM Series	A 20W B 27W C 40W D 60W	LV 120-277V HV 347-480V	4K 4000K 5K 5000K	D Dark Bronze B Black W White SG Silver Gray	M With Sensor Blank Without Sensor	D 1-10V Dimmable Blank NO Dimmable	EM With Battery Blank Without Battery

- Note: 1. 20W and 27W are limited to 120-277V input only.  
2. 20W only for NO Dimmable.  
3. Only the DIM has emergency battery options.