

Project:	
Type:	
Catalog #:	

TROFFERS GEN 2

Product Description

The FME Troffer produces high efficacy performance with energy savings and dimming capability. These fixtures are set recessed into the ceiling typically in a grid pattern to provide bright uniform lighting output enhancing overall illumination in multiple applications.



FEATURES

2x2 2x4

25W 34W

4000K / 5000K

Efficacy up to 134 LPW

7 Year Warranty

0 – 10V Dimming

Rated Life 75,000 hours

Operating Temperature
-20°C to 50°C

Construction & Installation

Beautiful white matte finish constructed with a high gauge durable body construction to withstand industrial commercial warehousing environments. The frosted prismatic polycarbonate lens to provide even light distribution with no diode visibility or glare. Ability to install in most standard T-bar ceiling grid system.

Electrical & Operations

Our Troffer series is universal voltage (120-277V) with a reliable driver for easy installation. Can operate in temperatures as low as -20°C and has high as 50°C. Fixture utilizes high-efficacy LED packages to maintain cool temperatures for a long lifespan

Applications

A wide variety of indoor use cases including schools, office buildings, banks, retail stores and other indoor applications with a grid system

Certification

UL Listed. All components have UL certification. UL Class 2. Driver: SCP, OTP, OVP protection, FCC Part 15 Class B, UL8750 Class 2. DLC Premium

Warranty

7 year warranty with a 75,000 hour rated L70. See warranty documentation for more detail information.

ORDERING INFORMATION

Example: FME-TR-24-34W-4K


Nomenclature	Series	Form Factor	Wattage	Color Temp.
FME	TR	24	34W	4000K
	JBCB = Troffer	A = 2x2	25W = 25 Watts	3500K = 3500K
	Series	B = 2x4	34W = 34 Watts	4000K = 4000K 5000K = 5000K




SPECIFICATION	
PERFORMANCE SUMMARY	
Input Voltage	120-277V
Input Frequency	50/60 Hz
Wattage	See Performance table
Lumens	See Performance Table
Efficacy	>130 LPW
CRI	83+
CCT	4000K / 5000K
Rated Life	75,000 Hr
L70	>72,000 Hr
Power Factor	>0.9
THD	<20%
Dimming	0-10V
Operating Temp.	-20°C to 50°C

DIMENSIONS

2X4



2X2



CARTON DIMENSIONS AND WEIGHT

Model	Carton	Weight	PCS/BOX
2x2	26" x 4.25" x 26"	8.8 LBS	1 pcs
2x4	50" x 4.5" x 26"	16.25 LBS	1 pcs

PERFORMANCE DETAILS

Form Factor	Catalog No.	Rated Wattage	Tested Wattage	4000K		5000K	
				Total Lumens	Efficacy LPW	Total Lumens	Efficacy LPW
2X2	2x2 35W	25W	25W	3125 lm	125	3150 lm	126
2X4	2x4 34W	34W	34W	4420 lm	130	4556 lm	134