


Project:	
Type:	
Catalog#:	



STANDARD



This billboard unit provides high light levels with even distribution, for spot lighting. The unit is weather resistant and suitable for most outdoor applications.

Construction:

- Housing is made of heavy gauge extruded aluminum with die cast end plates and splice box fittings. Housing interior is finished in a baked enamel finish for maximum reflectivity and durability. Splice box is threaded for 3/4" conduit and contains adjusting screws for housing. Lens is clear smooth slide-on acrylic that resists yellowing.

Electrical

All units are furnished with UL Listed Class P thermally protected ballast. Other voltages are available upon request. Fixtures meet requirements for UL Luminaire Standard # 1598. All units comply with National Energy Standard. All units are UL certified damp and wet location


Mounting

Units are designed to be conduit mounted either individually, tandem, or in a continuous run

WARRANTY & LISTINGS

- 5-year warranty of all electronics and housing.
- UL Certified for damp location

DIMENSIONS



Fixture Length

# of Lamps	T5HO	Length
1 or 2	F54T5HO	53"
TANDEM		
Single or Double	F54T5HO	101"

For Tandem Units Multiply Unit above by 2

Ordering Guide

OD-LED
Series
OD-LED
*0-10v low voltage dimming standard per fixture
*Higher and custom lumen packages available upon request

*Call Factory for lumen options of 6FT models

Size

4 = 4FT
6 = 6FT
8 = 8FT

Lumens

4FT	8FT
3220 (17W)	3220 (17W)
4480 (24W)	4480 (24W)
5705 (30W)	5705 (30W)
6910 (37W)	6910 (37W)
8640 (48W)	8640 (48W)
11797 (70W)	11797 (70W)
	13820 (74W)
	17280 (96W)
	23594 (140W)

Color

3K
35K
4K
5K

Options

EMB = emergency ballast
FR = Frosted lens over LED Boards

max weight= 11lbs/53" 15lbs/101"