

Project:	
Type:	
Catalog #:	

STANDARD	OPTIONAL



ILLUMINATION

- Two fully adjustable, ultra bright 3.3 watt high performance MR-16 base LED lamp heads for optimized center-to-center spacing.

ELECTRICAL

- Powered from low voltage 6V/12V DC power source with low voltage wiring (not provided).

MOUNTING

- Universal knockout pattern on back provided with gasket for watertight seal for back mount.
- Distance of maximum run is determined by system voltage, wire gauge, and total maximum wattage on the run.
- Suitable for wall or ceiling mount.

HOUSING

- Housing is reinforced polycarbonate construction in white, gray or black finish.
 - Corrosion-resistant enclosure with one piece, high-impact resistant, UV stabilized polycarbonate lens and molded gasket with stainless steel screws.
- Knockout's provided for conduit feed applications.



OPTIONS

- TP: Tamper-proof hardware helps discourage unauthorized access to the unit.

WARRANTY / LISTING

- Five year warranty.
- UL listed with approved FME Lighting Products.
- IP66 rated for Ingress protection.
- NEMA4X and NSF rated.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL certified for use in food service operations.

DIMENSIONS



*Contact FME for fixture compatibility. Reference individual unit equipment specification sheets for remote load capacity availability.

ORDERING INFORMATION

MODEL	HEADS	HOUSING COLOR	OPTIONS
YUM-R	1	W White	TP Tamper-Proof
	2	B Black	
		G Gray	