

Project:	
Type:	
Catalog #:	



PRODUCT FEATURES

- 20~90W, 4ft/8ft, 35K/4K/5K
- High lumen efficiency - up to 130lm/W
- DLC Premium Listed
- 0-10V dimming, dim to 10%
- V-hook and surface mounting available
- UL Listed for wet locations
- More than 100Khrs per L70-TM21 @70°C

APPLICATIONS

Vapor tight fixtures are built for powerful lighting in harsh environments like car washes, airports, tunnels, parking garages.




ZONAL LUMEN DISTRIBUTION

DEG	FLUX (lm)
0-10°	270.3
0-20°	1037.7
0-30°	2178.8
0-40°	3518
0-50°	4873.3
0-60°	6090.8
0-70°	7058
0-80°	7710.7
0-90°	8065.8
0-100°	8248.9
0-110°	8346.6
0-120°	8392.6
0-130°	8410.7
0-140°	8418
0-150°	8423.7
0-160°	8428.5
0-170°	8431.9
0-180°	8433

DIMENSIONS (mm)

4FT : 1200 x 90 x 80 / 2.0kg
8FT : 2400 x 90 x 80 / 3.5kg



ORDERING INFORMATION

MODEL	WATTAGE	CCT	VOLTAGE	DIMMING
PRS4 4FT Vapor Tight	A 38W	S 3500K	LV 120-277V	D 0-10 Dimming
PRS8 8FT Vapor Tight	B 45W	I 4000K		ND Non-Dimmable
	C 52W	C 5000K		
	D 75W			
	E 90W			