

Project:	
Type:	
Catalog #:	



## SPECIFICATIONS: INTERNAL

The ATOKA is 100% reliable, there are no internal parts to fail. It is a non-toxic, non-radioactive low profile exit solution. The ATOKA is visible at up to 50 feet.

## SPECIFICATIONS: EXTERNAL

**Construction:** Plastic photoluminescent panel, red or green lettering. Choice of a silver edgelit with an acrylic framing system (see BIXBY) or a silver frame. The ATOKA can be used for high and/or low level installations and has a 25 year life expectancy. It is visible at 50 feet during a blackout condition. The ATOKA meets current building codes, NFPA Life Safety Code 101 and OSHA requirements; International Building Code 2009/2012/2015/2018 and International Fire Code 2009/2012/2015/2018. Listed for LED lighting.

## SPECIFICATIONS: ELECTRICAL

**CIRCUIT:** Since there is no electricity required, the ATOKA is a safer signage solution, which saves on maintenance and energy costs.

**INSTALLATION:** Before installation it must be determined that there is a minimum of 5 Fc of LED, Fluorescent, metal halide or mercury vapor light on the face(s) of the sign at all times during building occupancy.




INDOOR | EXPLOSION PROOF | LEED POINTS QUALIFIED

## SPECIFICATIONS: MECHANICAL

The ATOKA series utilizes photoluminescent technology which absorbs and stores ambient light. It is a non-toxic, and non-radioactive low profile emergency lighting solution. The ATOKA features field adjustable chevrons and is constructed of ABS plastic with photoluminescent panel. The ATOKA is NON-TOXIC and NON-RADIOACTIVE which eliminates disposal fees.

## WARRANTY

The ATOKA comes with a 10 year factory warranty. Deliberate damage misuse, improper installation effectively cancel the warranty.



Series	Frame	Face No.	Lettering	Mounting
ATO	SF (silver aluminum frame)	1 (single)	GN (green)	B (mounting bracket)
		2 (double)	RD (red)	