

Project:	
Type:	
Catalog #:	

## STANDARD



## APPLICATIONS

5" & 6" Gimbal solution with integrated LED power supply and thermal management system combined in a single compact unit designed to fit most standard 5" & 6" recessed cans.

## ILLUMINATION

- Long life LEDs with up to 50,000 hours at 70% lumen maintenance.
- Choice of 2700K ( $\pm 145$ ), 4000K ( $\pm 275$ ) color temperature with 80 CRI.
- Produces 975-1050 lumens output from luminaire.
- Uses 1.18W high power, high quality LEDs.

## ELECTRICAL

- Dimmable to 10% with most dimmers.
- Lutron Maestro C-L MACL-153MR
- Lutron Skylark C-L SCL-153P
- Leviton Sureslide Cat.No.6674
- Lutron PD-6WCL
- Legrand Harmony HCL453PTCCC6
- Save 75% compared to incandescent sources.
- High efficiency driver with a power factor  $\geq .90$  with input power of 120V, 50-60Hz.
- Built-in LED Driver.
- Power consumption of 14 watts.
- Operation temperature of -20°C - 40°C (-4°F - 104°F).

## MOUNTING

- Easy installation with adjustable torsion spring.
- Torsion spring is designed to fit into 5" or 6" housing automatically without changing mounting tab.
- No tools required for installation.

## ORDERING INFORMATION

MODEL	OPTIONS		KELVIN RATING		LUMENS
BBB-LED56-GR-27K-ECO	GR	GIMBAL	27K	2700 K	975
BBB-LED56-GR-4K-ECO	GR	GIMBAL	4K	4000 K	1050



## HOUSING

- Compatible with most 5" and 6" housings.
- Compatible with insulated, non-insulated, and air-tight ceilings.
- Durable thermoplastic construction.
- E26 medium screw-base Edison connector provides easy retrofit of incandescent housings.

## WARRANTY/LISTING

- Tested in accordance with IESNA LM79 & LM80.
- ETL Listed for damp location.
- Energy Star qualified.
- Passes FCC Class B.
- Meets State of California Title 24 requirements.
- Five year warranty on all electronics and housing.

## DIMENSIONS

