

EB3000-TD

Fluorescent Emergency Ballast with Time Delay Feature



Project:	
Type:	
Catalog#:	

HOUSING

- Galvanized steel housing



ELECTRICAL

- Provides a minimum of 90 minutes of emergency illumination
- Provides a maximum lumen output of 3000 lumens
- Time delay enhancement specifically designed for programmed start AC ballasts to ensure proper restrike of lamps
- AC feature designed to eliminate deterioration of lamp life
- High-temperature nickel-cadmium battery, charger and electronic circuitry
- Dual voltage 120/277 VAC operation - Short circuit protection
- Solid-state charging indicator light
- Single-pole test switch
- Input Watts: 5.1W

INSTALLATION

- For use with either switched or unswitched fixture
- Ballast may be installed inside, on top, or remote from fixture
- Ballast may be remote at 1/2 distance recommended by AC ballast manufacturer (maximum 50')

BATTERY


- Ambient Temperature Rating 32°F - 122°F - Maintenance-Free Nickel-Cadmium Battery - Maximum recharge time: 24 hours
- Charging current: 280mA

CODE COMPLIANCE

- UL924 Listed for Damp Location
- UL Listed for retrofit/field installation
- NFPA Life Safety Code compliant
- Meets NEC and OSHA requirements

WARRANTY

- 5 Year warranty



ORDERING INFORMATION

Model

EB3000-TD

LAMP TYPE	WATTAGE
T5 (1L)	8-28
T5 (2L)	8-28
T5HO (1L)	39-54
T8 (1L)	17-59
T8 (2L)	17-40
T12 (1L)	20-215
T12 (2L)	20-40
4-PIN CFL (1L)	13-42
4-PIN CFL (2L)	13-42
4-PIN LONG CFL (1L)	18-55
4-PIN LONG CFL (2L)	18-50
T9 CIRCLINE (1L)	20-40
T9 CIRCLINE (2L)	20-40
U-BEND (1L) T8	32
U-BEND (2L) T8	32
U-BEND (1L) T12	34
U-BEND (2L) T12	34

LAMP	INITIAL LUMENS	
	1 LAMP	2 LAMP
T5 (14W)	1150	1200
T5 (21W)	1750	1800
T5 (28W)	2350	2425
T5HO (39W)	2700	2850
T5HO (54W)	2900	3000
T8 (17W)	1100	1150
T8 (32W)	2950	3000
T8 (59W)	2800	-
T12 (20W)	875	9000
T12 (40W)	2250	2400
T12 (110W)	2950	-
T12 (215W)	3000	-
4-PIN CFL (13W)	825	900
4-PIN CFL (18W)	1100	1200
4-PIN CFL (26W)	1500	1600
4-PIN CFL (32W)	2200	2300
4-PIN CFL (42W)	2450	2500
4-PIN LONG CFL (18W)	1250	1400
4-PIN LONG CFL (24W)	1750	1900
4-PIN LONG CFL (36W)	2200	2300
4-PIN LONG CFL (40W)	2350	2400
4-PIN LONG CFL (50W)	2250	2400
4-PIN LONG CFL (55W)	2500	-