

Project:	
Type:	
Catalog#:	

HOUSING

- Galvanized steel housing

ELECTRICAL

- Provides a minimum of 90 minutes of emergency illumination
- Provides a maximum lumen output of 1300 lumens
- Time delay enhancement specifically designed for programmed start AC ballasts to ensure proper restrike of lamps
- AC feature designed to eliminate deterioration of lamp life
- High-temperature nickel-cadmium battery, charger and electronic circuitry
- Dual voltage 120/277 VAC operation - Short circuit protection
- Solid-state charging indicator light
- Single-pole test switch
- Input Watts: 2.7W

INSTALLATION

- For use with either switched or unswitched fixture
- Ballast may be installed inside, on top, or remote from fixture
- Ballast may be remote at 1/2 distance recommended by AC ballast manufacturer (maximum 50')

BATTERY

- Ambient Temperature Rating 32°F - 122°F
- Maintenance-Free Nickel-Cadmium Battery
- Maximum recharge time: 24 hours
- Charging current: 280mA

CODE COMPLIANCE

- UL924 Listed for Damp Location
- UL Listed for retrofit/field installation
- NFPA Life Safety Code compliant
- Meets NEC and OSHA requirements


WARRANTY

- 5 Year warranty

ORDERING INFORMATION

Model

EBT5-1300-TD



LAMP TYPE	WATTAGE
T5 (1L)	14-28
T5HO (1L)	39-54
T8 (1L)	17-40
T12 (1L)	20-40
4-PIN CFL (1L)	13-42
4-PIN LONG CFL (1L)	18-50
T9 CIRCLINE	32-40

LAMP	INITIAL LUMENS
1 LAMP	
T5 (14W)	700
T5 (21W)	850
T5 (28W)	1100
T5HO (39W)	1200
T5HO (54W)	1300
T8 (17W)	950
T8 (32W)	1100
T12 (20W)	900
T12 (40W)	1200
4-PIN CFL (13W)	800
4-PIN CFL (18W)	950
4-PIN CFL (26W)	975
4-PIN CFL (32W)	1025
4-PIN CFL (42W)	1075
4-PIN LONG CFL (18W)	925
4-PIN LONG CFL (24W)	950
4-PIN LONG CFL (36W)	1025
4-PIN LONG CFL (40W)	1050
4-PIN LONG CFL (50W)	1100