



FME-L 300 (36,000) - HIGH BAY LIGHT

Project:	
Type:	
Catalog:	

STANDARD

The FME High Bay fixture can replace HPS and MH fixtures up to 750Watts. Typical mounting heights for this fixture are 35' to 50'. A variation of optics 30/50/100 allow for high lumen output on the work surface. The At 135 LPW the fixture will save up to 70% energy. L70 at 55C is 60,000 with full light output. This allows for the fixtures to be mounted in high heat application typically found in heavy industrial applications. This compact size and light-weight makes for an easy retrofit. Battery backup is available.



FEATURES

- Slim profile design, easy for installation
- UV rated powder paint coating
- Rotatable bracket made of stainless steel
- System efficacy up to 120 – 135 lm/W (Ra > 80)
- $\frac{1}{4}$ inch NPT pendant mount available for market
- Emergency back-up unit and motion sensor option available



APPLICATIONS

- Warehouse
- Factory
- Retail stores
- Commercial sites

SPECIFICATIONS

Input voltage:	AC 90-305V
	50/60Hz
Operation Temp:	-30°C to + 50°C
LED Lifetime (L70):	60,000 hours
Dimmable:	1-10V optional

ORDERING INFORMATION

Model	Lumens	Optics	CRI	Wattage	CCT
High Bay Light 200W	24,000	30/50	70/80	200	3/4/5/6K
High Bay Light 300W	36,000	30/50/100	70/80	500	3/4/5/6K