

LINR the outperformer

- High performance SMD design
- Efficacy up to 120lm/w
- Electrical: AC 100~277 V
- Energy saving up to 80%
- CCT: 5000K(3000K~6500K)
- CRI>80
- Superb uniformity
- Quality MEANWELL brand driver
- IP54 protection rating
- Standard beam angle 120°
- Die casting aluminum lamp house
- High quality optical plastic cover
- Operating temperature : -30~+50°C
- Body: Aluminum alloy
- Stainless steel screws

LINR Great Features:

- Patented Products
- Easier installation.
- Pretty appearance
- 120lm/w Samsung 2835 leds
- IES file and Dialux simulation can be provided
- Separate power supply box makes it convenient for customers to replace the driver




Model No.	LINR_100	LINR_150	LINR_100	LINR_160	LINR_240	LINR_320
Rated Power(W)	100W	150W	100W	160W	240W	320W
Lumen Efficiency	130lm/W					
Luminous Flux	12,000lm	18,000lm	12,000lm	19,200lm	28,800lm	38,400lm
LED Brand	Samsung 2835					
CCT	3000K-6500K					
Ra(CRI)	>80					
Input Voltage(V)	AC 100-277 V					
Driver Brand	MEANWELL/ROSEN					
IP Rating	IP54					
Beam Angle	120 Degree					
Working Temperature	-30°~+50°					
Product Size	624*426*120mm	924*426*120mm	1224*426*120mm	1224*426*120mm	1224*426*120mm	1224*426*120mm

Control Options

Add to the product part numbers to include these control options

1-10V	Motion Sensor	Daylight Sensor	Photocell Sensor	DALI	Zigbee
-------	---------------	-----------------	------------------	------	--------

Illuminance Chart



FME Lighting, LLC.

ADD: PO Box 488, Hockessin, De 19707

TEL: 302-307-2911

Email: Patrick@FMElighting.com

Mobile: 302-584-3652

WEB: www.fmelighting.com



LINR LED High Bay Light

Innovation over adaption

