

# STOCK ONLY Hazardous Location/Explosion Proof - USA Inventory



Inventory Levels as of 3/27/2025

FME LIGHTING | 877-234-8460 | info@fmelighting.com

| Series                                                     | Picture                                                                             | Model                                                                                                        | Wattage | Stock Available      | Lumens               | CCT           | Beam Angle        | Ratings                                                                                                                                            | Ambient Operation Temperature        |
|------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|---------|----------------------|----------------------|---------------|-------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|
| Solstice Series Area / Low-High Bay<br>Class I, Division I |    | SOL-5-LV-C-120-7-NPT-TR/PM-5Y-S<br>Pendant +Trunion   1x 3/4" without exposed power cord   100-277VAC        | 50W     | 80pcs                | 7000lm<br>(140LM/W)  | 5000K<br>Ra70 | 120°<br>(No Lens) | NEMA 4X<br>UL 1598, UL 1598A, UL 8750, UL 844<br>CSA C22.2 No. 137, CSA C22.2 No. 250.0<br>Temp. Code: T5,T6                                       | -40°C to + 65°C                      |
| Solstice Series Area / Low-High Bay<br>Class I, Division I |    | SOL-7-LV-C-120-7-NPT-TR/PM-5Y-S<br>Pendant +Trunion   1x 3/4" without exposed power cord   100-277VAC        | 70W     | 79pcs                | 9800lm<br>(140LM/W)  | 5000K<br>Ra70 | 120°<br>(No Lens) | NEMA 4X<br>UL 1598, UL 1598A, UL 8750, UL 844<br>CSA C22.2 No. 137, CSA C22.2 No. 250.0<br>Temp. Code: T5,T6                                       | -40°C to + 65°C<br>-40°C to + 60°C   |
| Rocket Series Flood Light<br>Class I, Division II          |    | ROC-24-LV-C-TYPEV-XP-5Y-S<br>Trunion   2x 3/4" without exposed power cord   100-277VAC                       | 240W    | 129pcs               | 36,000lm             | 5000K<br>Ra70 | 120°<br>(No Lens) | NEMA 4X<br>UL 1598, UL 1598A, UL 8750, UL 844<br>CSA C22.2 No. 137, CSA C22.2 No. 250.0<br>Temp. Code: T5,T6                                       | -40°C to 50°C (-40°F to 122°F)       |
| Nebula Series Low-High Bay<br>Class I, Division II         |    | NEB-10-LV-C-TYPEV-70CRI-NPT-TR/PM-5Y-S<br>Pendant +Trunion   1x 3/4" without exposed power cord   100-277VAC | 100W    | 205pcs<br>Dimmable   | 10125lm              | 5000K<br>Ra70 | 120°<br>(No Lens) | NEMA 4X<br>UL 1598, UL 1598A, UL 8750, UL 844, UL924<br>CSA C22.2 No. 137, CSA C22.2 No. 250.0 CSA C22.2 No. 141<br>Temp. Code: T5,T6              | -40° to +60°C<br>MAX: -40°C to 65°C  |
| Nebula Series Low-High Bay<br>Class I, Division II         |    | NEB-15-LV-C-TYPEV-70CRI-NPT-TR/PM-5Y-S<br>Pendant +Trunion   1x 3/4" without exposed power cord   100-277VAC | 150W    | 361pcs<br>Dimmable   | 20250lm              | 5000K<br>Ra70 | 120°<br>(No Lens) | NEMA 4X<br>UL 1598, UL 1598A, UL 8750, UL 844, UL924<br>CSA C22.2 No. 137, CSA C22.2 No. 250.0 CSA C22.2 No. 141<br>Temp. Code: T5,T6              | -40° to +55°<br>MAX: -40°C to 65°C   |
| Nebula Series Low-High Bay<br>Class I, Division II         |    | NEB-24-LV-C-TYPEV-70CRI-NPT-TR/PM-5Y-S<br>Pendant +Trunion   1x 3/4" without exposed power cord   100-277VAC | 240W    | 221pcs<br>Dimmable   | 32400lm              | 5000K<br>Ra70 | 120°<br>(No Lens) | NEMA 4X<br>UL 1598, UL 1598A, UL 8750, UL 844, UL924<br>CSA C22.2 No. 137, CSA C22.2 No. 250.0 CSA C22.2 No. 141<br>Temp. Code: T5,T6              | -40°C to +45°C<br>MAX: -40°C to 65°C |
| LIH Series Linear Light<br>Class I, Division II            |    | LIH-5-LV-50-D-DL-B-TM/PM-3/4-S<br>Pendant +Trunion   1x 3/4" without exposed power cord   100-277VAC         | 50W     | 61pcs<br>Dimmable    | 8000lm<br>(160LM/W)  | 5000K<br>Ra70 | Diffused Cover    | NEMA 4X<br>UL 844, UL:50/E,UL 1598/A, UL 8750, UL924<br>CSA C22.2 No. 137, CSA C22.2 No. 250.0 CSA C22.2 No. 141, C22.2 No. 94.1, C22.2 No.94.2    | -40°C to + 45°C (-40°F to +113°F)    |
| LIH Series Linear Light<br>Class I, Division II            |    | LIH-10-LV-50-D-DL-B-TM/PM-3/4-S<br>Pendant +Trunion   1x 3/4" without exposed power cord   100-277VAC        | 100W    | 34pcs<br>Dimmable    | 16000lm<br>(160LM/W) | 5000K<br>Ra70 | Diffused Cover    | NEMA 4X<br>UL 844, UL:50/E,UL 1598/A, UL 8750, UL924<br>CSA C22.2 No. 137, CSA C22.2 No. 250.0 CSA C22.2 No. 141, C22.2 No. 94.1, C22.2 No.94.2    | -40°C to + 40°C (-40°F to +104°F)    |
| Galaxy Series Flood Light<br>Class I, Division II          |   | FME-GAX-G-6-B-C-P-ND<br>Glass Lens                                                                           | 60W     | Sold Out             | 8100lm               | 5000K         | 120°              | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3                  | -104°F to 122°F (- 40°C to +40°C)    |
| Galaxy Series Flood Light<br>Class I, Division II          |  | FME-GAX-G-6-A-C-P-D<br>Glass Lens                                                                            | 60W     | Sold Out<br>Dimmable | 8100lm               | 5000K         | 120°              | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3Other: IP66 IK10  | -104°F to 122°F (- 40°C to +40°C)    |
| Galaxy Series Flood Light<br>Class I, Division II          |  | FME-GAX-G-6L-A-C-P-ND<br>Glass Lens<br>6L (60W) = 12.5x9.45x6.5in                                            | 60W     | 110pcs               | 8100lm               | 5000K         | 120°              | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3Other: IP66 IK10  | -104°F to 122°F (- 40°C to +40°C)    |
| Galaxy Series Flood Light<br>Class I, Division II          |  | FME-GAX-G-6L-B-I-P-D<br>Glass Lens<br>6L (60W) = 12.5x9.45x6.5in                                             | 60W     | 60pcs<br>4000K       | 8100lm               | 4000K         | 120°              | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10 | -104°F to 122°F (- 40°C to +40°C)    |
| Galaxy Series Flood Light<br>Class I, Division II          |  | FME-GAX-G-6L-B-C-P-D<br>Glass Lens<br>6L (60W) = 12.5x9.45x6.5in                                             | 60W     | 30pcs<br>200-480V    | 8100lm               | 5000K         | 120°              | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10 | -104°F to 122°F (- 40°C to +40°C)    |

TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

FME Lighting | 877 - 234 - 8460 | info@fmelighting.com | 1

| Series                                                | Picture                                                                             | Model                                      | Wattage | Stock Available                                                | Lumens   | CCT   | Beam Angle | Ratings                                                                                                                                            | Ambient Operation Temperature     |
|-------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------|---------|----------------------------------------------------------------|----------|-------|------------|----------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|
| Galaxy Series Flood Light <b>Class I, Division II</b> |     | FME-GAX-G-8-A-I-P-ND<br><i>Glass Lens</i>  | 80W     | <b>Sold Out</b><br><b>4000K</b>                                | 8100lm   | 4000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10 | -104°F to 122°F (- 40°C to +40°C) |
| Galaxy Series Flood Light <b>Class I, Division II</b> |    | FME-GAX-G-8-A-C-P-D<br><i>Glass Lens</i>   | 80W     | <b>90pcs</b><br><b>100pcs ETA to BG 5/5</b><br><b>Dimmable</b> | 10400lm  | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10 | -104°F to 122°F (- 40°C to +40°C) |
| Galaxy Series Flood Light <b>Class I, Division II</b> |    | FME-GAX-G-10-A-C-P-D<br><i>Glass Lens</i>  | 100W    | <b>273pcs</b><br><b>Dimmable</b>                               | 13500lm  | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10 | -104°F to 122°F (- 40°C to +40°C) |
| Galaxy Series Flood Light <b>Class I, Division II</b> |    | FME-GAX-G-10-A-I-P-ND<br><i>Glass Lens</i> | 100W    | <b>43pcs</b><br><b>4000K</b>                                   | 13500lm  | 4000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10 | -104°F to 122°F (- 40°C to +40°C) |
| Galaxy Series Flood Light <b>Class I, Division II</b> |    | FME-GAX-G-10-B-C-P-D<br><i>Glass Lens</i>  | 100W    | <b>65pcs</b><br><b>DIM 200-480V</b>                            | 13500 lm | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10 | -104°F to 122°F (- 40°C to +40°C) |
| Galaxy Series Flood Light <b>Class I, Division II</b> |    | FME-GAX-G-15-A-C-P-ND<br><i>Glass Lens</i> | 150W    | <b>Sold Out</b>                                                | 20250lm  | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10 | -104°F to 122°F (- 40°C to +40°C) |
| Galaxy Series Flood Light <b>Class I, Division II</b> |    | FME-GAX-G-15-A-C-P-D<br><i>Glass Lens</i>  | 150W    | <b>320pcs</b><br><b>Dimmable</b>                               | 20250lm  | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10 | -104°F to 122°F (- 40°C to +40°C) |
| Galaxy Series Flood Light <b>Class I, Division II</b> |    | FME-GAX-G-15-B-C-P-D<br><i>Glass Lens</i>  | 150W    | <b>Sold Out</b><br><b>200-480V</b>                             | 20250lm  | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10 | -104°F to 122°F (- 40°C to +40°C) |
| Galaxy Series Flood Light <b>Class I, Division II</b> |    | FME-GAX-G-20-A-C-P-ND<br><i>Glass Lens</i> | 200W    | <b>Sold Out</b>                                                | 28000lm  | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10 | -104°F to 122°F (- 40°C to +40°C) |
| Galaxy Series Flood Light <b>Class I, Division II</b> |  | FME-GAX-G-20-A-C-P-D<br><i>Glass Lens</i>  | 200W    | <b>40pcs</b><br><b>4000K</b>                                   | 28000lm  | 4000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10 | -104°F to 122°F (- 40°C to +40°C) |
| Galaxy Series Flood Light <b>Class I, Division II</b> |  | FME-GAX-G-20-A-C-P-D<br><i>Glass Lens</i>  | 200W    | <b>580pcs</b><br><b>Dimmable</b>                               | 28000lm  | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10 | -104°F to 122°F (- 40°C to +40°C) |
| Galaxy Series Flood Light <b>Class I, Division II</b> |  | FME-GAX-G-25-A-C-P-D<br><i>Glass Lens</i>  | 250W    | <b>45pcs</b><br><b>Dimmable</b>                                | 35,000lm | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10 | -104°F to 122°F (- 40°C to +40°C) |
| Galaxy Series Flood Light <b>Class I, Division II</b> |  | FME-GAX-G-30-A-C-P-D<br><i>Glass Lens</i>  | 300W    | <b>Sold Out</b><br><b>Dimmable</b>                             | 42000lm  | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10 | -104°F to 122°F (- 40°C to +40°C) |
| Galaxy Series Flood Light <b>Class I, Division II</b> |  | FME-GAX-G-40-A-C-P-D<br><i>Glass Lens</i>  | 400W    | <b>60pcs</b><br><b>Dimmable</b>                                | 56000lm  | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10 | -104°F to 122°F (- 40°C to +40°C) |



TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

| Series                                      | Picture                                                                             | Model                   | Wattage | Stock Available                                | Lumens  | CCT   | Beam Angle | Ratings                                                                                                                                            | Ambient Operation Temperature     |
|---------------------------------------------|-------------------------------------------------------------------------------------|-------------------------|---------|------------------------------------------------|---------|-------|------------|----------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|
| Moon Series Highbay<br>Class I, Division II |     | FME-M00-4-A-I-ND-5Y     | 40W     | 13pcs<br>4000K                                 | 8100 lm | 4000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3                  | -104°F to 122°F (- 40°C to +50°C) |
| Moon Series Highbay<br>Class I, Division II |    | FME-M00-6-A-C-P-ND-5Y   | 60W     | Sold Out                                       | 8100lm  | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3                  | -104°F to 122°F (- 40°C to +50°C) |
| Moon Series Highbay<br>Class I, Division II |    | FME-M00-6-A-C-P-D-5Y    | 60W     | Sold Out<br>97pcs ETA to WH 5/5<br>Dimmable    | 8100lm  | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3                  | -104°F to 122°F (- 40°C to +50°C) |
| Moon Series Highbay<br>Class I, Division II |    | FME-M00-6L-A-C-P-D-5Y   | 60W     | Sold Out<br>Dimmable                           | 8100lm  | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10 | -104°F to 122°F (- 40°C to +50°C) |
| Moon Series Highbay<br>Class I, Division II |    | FME-M00-8-A-C-P-ND-5Y   | 80W     | Sold Out                                       | 10800lm | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10 | -104°F to 122°F (- 40°C to +50°C) |
| Moon Series Highbay<br>Class I, Division II |    | FME-M00-8-A-I-P-D-5Y    | 80W     | 10pcs<br>50pcs ETA to WH 5/5<br>Dimmable 4000K | 10800lm | 4000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10 | -104°F to 122°F (- 40°C to +50°C) |
| Moon Series Highbay<br>Class I, Division II |    | FME-M00-8-A-C-P-D-5Y    | 80W     | 500pcs<br>Dimmable                             | 10800lm | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10 | -104°F to 122°F (- 40°C to +50°C) |
| Moon Series Highbay<br>Class I, Division II |    | FME-M00-10- A-C-P-ND-5Y | 100W    | Sold Out                                       | 14000lm | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10  | -104°F to 104°F (- 40°C to +40°C) |
| Moon Series Highbay<br>Class I, Division II |    | FME-M00-10- A-C-P-D-5Y  | 100W    | 90pcs<br>Dimmable                              | 14000lm | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10  | -104°F to 104°F (- 40°C to +40°C) |
| Moon Series Highbay<br>Class I, Division II |  | FME-M00-15-A-C-P-ND-5Y  | 150W    | Sold Out                                       | 21000lm | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10  | -104°F to 104°F (- 40°C to +40°C) |
| Moon Series Highbay<br>Class I, Division II |  | FME-M00-15-A-I-P-D-5Y   | 150W    | 26pcs<br>Dimmable 4000K                        | 21000lm | 4000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10  | -104°F to 104°F (- 40°C to +40°C) |
| Moon Series Highbay<br>Class I, Division II |  | FME-M00-15-A-C-P-D-5Y   | 150W    | 230pcs<br>Dimmable                             | 21000lm | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10  | -104°F to 104°F (- 40°C to +40°C) |
| Moon Series Highbay<br>Class I, Division II |  | FME-M00-15-B-C-P-D-5Y   | 150W    | 18pcs<br>Dimmable 200-480V                     | 21000lm | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10  | -104°F to 104°F (- 40°C to +40°C) |
| Moon Series Highbay<br>Class I, Division II |  | FME-M00-20-B-C-P-ND-5Y  | 200W    | Sold Out                                       | 28000lm | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10  | -104°F to 104°F (- 40°C to +40°C) |



TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

| Series                                      | Picture                                                                             | Model                     | Wattage | Stock Available                            | Lumens  | CCT   | Beam Angle | Ratings                                                                                                                                                                              | Ambient Operation Temperature                                                      |
|---------------------------------------------|-------------------------------------------------------------------------------------|---------------------------|---------|--------------------------------------------|---------|-------|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|
| Moon Series Highbay<br>Class I, Division II |     | FME-M00-20-A-I-P-ND-5Y    | 200W    | <b>Sold Out</b><br>4000K                   | 28000lm | 4000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII<br>Temp. Code: T3<br>Other: IP66 IK10                              | -104°F to 104°F (- 40°C to +40°C)                                                  |
| Moon Series Highbay<br>Class I, Division II |    | FME-M00-20-A-C-P-D-5Y     | 200W    | <b>178pcs</b><br>Dimmable                  | 28000lm | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII<br>Temp. Code: T3<br>Other: IP66 IK10                              | -104°F to 104°F (- 40°C to +40°C)                                                  |
| Moon Series Highbay<br>Class I, Division II |    | FME-M00-20-B-C-P-D-5Y     | 200W    | <b>45pcs</b><br>Dimmable 200-480V          | 28000lm | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII<br>Temp. Code: T3<br>Other: IP66 IK10                              | -104°F to 104°F (- 40°C to +40°C)                                                  |
| Moon Series Highbay<br>Class I, Division II |    | FME M00-25-A-C-P-D-5      | 250W    | <b>15pcs</b><br>ETA to WH 4/15<br>Dimmable | 33750lm | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III<br>Temp. Code: T3Other: IP66 IK10                                 | -104°F to 104°F (- 40°C to +40°C)                                                  |
| Moon Series Highbay<br>Class I, Division II |    | FME-M00-30-A-C-P-D-5Y     | 300W    | <b>29pcs</b><br>Dimmable                   | 42000lm | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III<br>Temp. Code: T3Other: IP66 IK10                                 | -104°F to 104°F (- 40°C to +40°C)                                                  |
| Moon Series Highbay<br>Class I, Division II |    | FME-M00-40-A-C-P-D-5Y     | 400W    | <b>3pcs</b><br>Dimmable                    | 56000lm | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III<br>Temp. Code: T3Other: IP66 IK10                                 | -104°F to 104°F (- 40°C to +40°C)                                                  |
| Star Series Highbay<br>Class I, Division I  |    | FME-STA-4-42-A-C-R-D-5Y   | 40W     | <b>30pcs</b><br>Dimmable                   | 5400lm  | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II,Group E,F,G ClassIII<br>Temp. Code: T4<br>Other: IP66 IK1 | 277VAC, -40°C to 55°C (-104°F to 131°F)<br>120VAC, -40°C to 40°C (-104°F to 104°F) |
| Star Series Highbay<br>Class I, Division I  |    | FME-STA-6-42-A-I-R-ND-5Y  | 60W     | <b>35pcs</b><br>4000K                      | 8400lm  | 4000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II,Group E,F,G ClassIII<br>Temp. Code: T4<br>Other: IP66 IK1 | 277VAC, -40°C to 55°C (-104°F to 131°F)<br>120VAC, -40°C to 40°C (-104°F to 104°F) |
| Star Series Highbay<br>Class I, Division I  |    | FME-STA-6-42-A-C-R-D-5Y   | 60W     | <b>205pcs</b><br>Dimmable                  | 8400lm  | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II,Group E,F,G ClassIII<br>Temp. Code: T4<br>Other: IP66 IK1 | 277VAC, -40°C to 55°C (-104°F to 131°F)<br>120VAC, -40°C to 40°C (-104°F to 104°F) |
| Star Series Highbay<br>Class I, Division I  |  | FME-STA-8-42-A-I-R-ND-5Y  | 80W     | <b>Sold Out</b><br>4000K                   | 11200lm | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II,Group E,F,G ClassIII<br>Temp. Code: T4<br>Other: IP66 IK1 | 277VAC, -40°C to 55°C (-104°F to 131°F)<br>120VAC, -40°C to 40°C (-104°F to 104°F) |
| Star Series Highbay<br>Class I, Division I  |  | FME-STA-8-42-A-C-R-D-5Y   | 80W     | <b>170pcs</b><br>Dimmable                  | 11200lm | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II,Group E,F,G ClassIII<br>Temp. Code: T4<br>Other: IP66 IK1 | 277VAC, -40°C to 55°C (-104°F to 131°F)<br>120VAC, -40°C to 40°C (-104°F to 104°F) |
| Star Series Highbay<br>Class I, Division I  |  | FME-STA-10-42-A-C-R-ND-5Y | 100W    | <b>Sold Out</b>                            | 13500lm | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II,Group E,F,G Class III<br>Temp. Code: T4 Other: IP66 IK10  | 277VAC, -40°C to 55°C (-104°F to 131°F)<br>120VAC, -40°C to 40°C (-104°F to 104°F) |
| Star Series Highbay<br>Class I, Division I  |  | FME-STA-10-42-A-I-R-ND-5Y | 100W    | <b>70pcs</b><br>4000K                      | 13500lm | 4000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II,Group E,F,G Class III<br>Temp. Code: T4 Other: IP66 IK10  | 277VAC, -40°C to 55°C (-104°F to 131°F)<br>120VAC, -40°C to 40°C (-104°F to 104°F) |
| Star Series Highbay<br>Class I, Division I  |  | FME-STA-10-42-A-C-R-D-5Y  | 100W    | <b>350pcs</b><br>Dimmable                  | 13500lm | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II,Group E,F,G Class III<br>Temp. Code: T4 Other: IP66 IK10  | 277VAC, -40°C to 55°C (-104°F to 131°F)<br>120VAC, -40°C to 40°C (-104°F to 104°F) |



TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

| Series                                                      | Picture                                                                             | Model                                                       | Wattage | Stock Available                              | Lumens   | CCT   | Beam Angle | Ratings                                                                                                                                                                           | Ambient Operation Temperature                                                      |
|-------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------|---------|----------------------------------------------|----------|-------|------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|
| Star Series Highbay<br>Class I, Division I                  |     | FME-STA-15-42-B-I-R-D-5Y                                    | 150W    | 30pcs<br>ETA to WH 4/15<br>Dimmable 200-480V | 20250lm  | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 | 277VAC, -40°C to 55°C (-104°F to 131°F)<br>120VAC, -40°C to 40°C (-104°F to 104°F) |
| Star Series Highbay<br>Class I, Division I                  |    | FME-STA-15-42-A-C-R-D-5Y                                    | 150W    | 210pcs<br>Dimmable                           | 20250lm  | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 | 277VAC, -40°C to 55°C (-104°F to 131°F)<br>120VAC, -40°C to 40°C (-104°F to 104°F) |
| Star Series Highbay<br>Class I, Division I                  |    | FME-STA-15-42-A-I-R-ND-5Y                                   | 150W    | 40pcs<br>4000K                               | 20250lm  | 4000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 | 277VAC, -40°C to 55°C (-104°F to 131°F)<br>120VAC, -40°C to 40°C (-104°F to 104°F) |
| Star Series Highbay<br>Class I, Division I                  |    | FME-STA-20-42-A-I-R-ND-5Y                                   | 200W    | 40pcs<br>4000K                               | 27000 lm | 4000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 | 277VAC, -40°C to 55°C (-104°F to 131°F)<br>120VAC, -40°C to 40°C (-104°F to 104°F) |
| Star Series Highbay<br>Class I, Division I                  |    | FME-STA-20-42-A-I-R-D-5Y                                    | 200W    | 40pcs<br>Dimmable                            | 27000 lm | 4000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 | 277VAC, -40°C to 55°C (-104°F to 131°F)<br>120VAC, -40°C to 40°C (-104°F to 104°F) |
| Star Series Highbay<br>Class I, Division I                  |    | FME-STA-20-42-B-C-R-D-5Y                                    | 200W    | Sold Out<br>Dimmable 200-480V                | 27000 lm | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 | 277VAC, -40°C to 55°C (-104°F to 131°F)<br>120VAC, -40°C to 40°C (-104°F to 104°F) |
| Star Series Highbay<br>Class I, Division I                  |    | FME-STA-10-42-A-C-R-D-5Y-OPGG<br>with Frosted Globe & Guard | 100W    | 20pcs<br>Dimmable                            | 13500lm  | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 | 277VAC, -40°C to 55°C (-104°F to 131°F)<br>120VAC, -40°C to 40°C (-104°F to 104°F) |
| Star Series Highbay<br>Class I, Division I                  |    | FME-STA-24-42-A-C-R-D-5Y                                    | 240W    | Sold Out<br>Dimmable                         | 32400 lm | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 | 277VAC, -40°C to 55°C (-104°F to 131°F)<br>120VAC, -40°C to 40°C (-104°F to 104°F) |
| Star Series Highbay<br>Class I, Division I                  |    | FME-STA-25-42-A-C-R-D-5Y                                    | 250W    | 110pcs<br>Dimmable                           | 35000lm  | 5000K | 120°       | Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10                                                              | 277VAC, -40°C to 55°C (-104°F to 131°F)<br>120VAC, -40°C to 40°C (-104°F to 104°F) |
| Earth Series Flood<br>Light/High Bay Class I,<br>Division I |  | FME-EAT-G-6-A-C-P-ND-5Y<br>Glass Lens                       | 60W     | 150pcs                                       | 8100lm   | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 | 104°F to 131°F (-<br>40°C to +55°C)                                                |
| Earth Series Flood<br>Light/High Bay Class I,<br>Division I |  | FME-EAT-G-6-A-I-P-ND-5Y<br>Glass Lens                       | 80W     | 10pcs<br>4000K                               | 8100lm   | 4000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 | 104°F to 131°F (-<br>40°C to +55°C)                                                |
| Earth Series Flood<br>Light/High Bay Class I,<br>Division I |  | FME-EAT-G-8-A-C-P-D-5Y<br>Glass Lens                        | 80W     | 135pcs<br>Dimmable                           | 11200lm  | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 | -104°F to 131°F (- 40°C to +55°C)                                                  |
| Earth Series Flood<br>Light/High Bay Class I,<br>Division I |  | FME-EAT-G-10-A-C-P-ND-5Y<br>Glass Lens                      | 100W    | 2pcs                                         | 13500lm  | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 | -104°F to 131°F (- 40°C to +55°C)                                                  |
| Earth Series Flood<br>Light/High Bay Class I,<br>Division I |  | FME-EAT-G-10-A-C-P-D-5<br>Glass Lens                        | 100W    | 123pcs<br>Dimmable                           | 13500lm  | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 | -104°F to 131°F (- 40°C to +55°C)                                                  |


TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

| Series                                                                           | Picture                                                                             | Model                                                                | Wattage | Stock Available                                                 | Lumens          | CCT   | Beam Angle | Ratings                                                                                                                                                                              | Ambient Operation Temperature     |
|----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------|---------|-----------------------------------------------------------------|-----------------|-------|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|
| Earth Series Flood Light/High Bay <b>Class I, Division I</b>                     |     | FME-EAT-G-10-A-I-P-ND-5<br><i>Glass Lens</i>                         | 150W    | <b>30pcs</b><br><b>ETA to WH 4/15</b><br><b>4000K</b>           | 20250lm         | 4000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4<br>Other: IP66 IK10 | -104°F to 131°F (- 40°C to +55°C) |
| Earth Series Flood Light/High Bay <b>Class I, Division I</b>                     |    | FME-EAT-G-15-A-C-P-D-5Y<br><i>Glass Lens</i>                         | 150W    | <b>100pcs</b><br><b>Dimmable</b>                                | 20250lm         | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4<br>Other: IP66 IK10 | -104°F to 131°F (- 40°C to +55°C) |
| Earth Series Flood Light/High Bay <b>Class I, Division I</b>                     |    | FME-EAT-G-15-B-C-P-ND-5Y<br><i>Glass Lens</i>                        | 150W    | <b>15pcs</b><br><b>50pcs ETA to WH 4/15</b><br><b>200-480V</b>  | 20250lm         | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4<br>Other: IP66 IK10 | -104°F to 131°F (- 40°C to +55°C) |
| MRT Series   Maritron Flanged Ceiling Surface Mount, <b>Class I, Division II</b> |    | MRT-B-4-LV1-C-D-CM<br><i>Includes 1 Meter Chains and Lift rings</i>  | 40W     | <b>28pcs</b><br><b>Dimmable</b>                                 | 5200lm<br>1X4   | 5000K | 120°       | Marine:UL 1598,UL844,UL924 UL 844: Class I, DivisionII, GroupA,B,C, D<br>Temp.Code: T4 Other:IP66 IK10                                                                               | -40°C to 60°C                     |
| MRT Series   Maritron Flanged Ceiling Surface Mount, <b>Class I, Division II</b> |    | MRT-C-4-LV1-C-D-CM<br><i>Includes 1 Meter Chains and Lift rings</i>  | 40W     | <b>43pcs</b><br><b>Dimmable</b>                                 | 5200lm<br>2X2   | 5000K | 120°       | Marine:UL 1598,UL844,UL924 UL 844: Class I, DivisionII, GroupA,B,C, D<br>Temp.Code: T4 Other:IP66 IK10                                                                               | -40°C to 60°C                     |
| MRT Series   Maritron Flanged Ceiling Surface Mount, <b>Class I, Division II</b> |    | MRT-D-6-LV1-C-D-CM<br><i>Includes 1 Meter Chains and Lift rings</i>  | 60W     | <b>20pcs</b><br><b>Dimmable</b>                                 | 7800lm<br>2X4   | 5000K | 120°       | Marine:UL 1598,UL844,UL924 UL 844: Class I, DivisionII, GroupA,B,C, D<br>Temp.Code: T4 Other:IP66 IK10                                                                               | -40°C to 60°C                     |
| MRT Series   Maritron Flanged Ceiling Surface Mount, <b>Class I, Division II</b> |    | MRT-D-10-LV1-C-D-CM<br><i>Includes 1 Meter Chains and Lift rings</i> | 100W    | <b>8pcs</b><br><b>Dimmable</b>                                  | 14000 lm<br>2X4 | 5000K | 120°       | Marine:UL 1598,UL844,UL924 UL 844: Class I, DivisionII, GroupA,B,C, D<br>Temp.Code: T4 Other:IP66 IK10                                                                               | -40°C to 60°C                     |
| Nova Series   Coming Soon, <b>Class I, Division II</b>                           |    | Coming Soon<br><i>Trunnion mount</i>                                 | 80W     | <b>53pcs</b><br><b>Dimmable</b>                                 | 10800lm         | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D<br>ClassII, Division I & II, Group E,F,G ClassIII<br>Temp. Code: T5/T4 Other: IP66 IK10                            | -104°F to 122°F (-40°C to +40°C)  |
| Mercury Series Highbay <b>Class I, Division I</b>                                |   | FME-MER-10-A-I-R-ND-5Y                                               | 100W    | <b>42pcs</b>                                                    | 13500lm         | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4<br>Other: IP66 IK10 | -104°F to 140°F (- 40°C to +60°C) |
| Mercury Series Highbay <b>Class I, Division I</b>                                |  | FME-MER-15-A-I-R-ND-5Y                                               | 150W    | <b>8pcs</b>                                                     | 20250lm         | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4<br>Other: IP66 IK10 | -104°F to 140°F (- 40°C to +60°C) |
| Mars Series Jelly Jar <b>Class I, Division I</b>                                 |  | FME-MAR-2-A-C-ND-5Y-CGG<br><i>Clear Globe w/ Wire Guard</i>          | 20W     | <b>10pcs</b>                                                    | 2700lm          | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4<br>Other: IP66 IK10 | -104°F to 140°F (- 40°C to +60°C) |
| Mars Series Jelly Jar <b>Class I, Division I</b>                                 |  | FME-MAR-3-A-C-P-ND-5Y-CGG<br><i>Clear Globe w/ Wire Guard</i>        | 30W     | <b>Sold Out</b>                                                 | 4050 lm         | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4<br>Other: IP66 IK10 | -104°F to 140°F (- 40°C to +60°C) |
| Mars Series Jelly Jar <b>Class I, Division I</b>                                 |  | FME-MAR-3-A-C-P-D-5Y-CGG<br><i>Clear Globe w/ Wire Guard</i>         | 30W     | <b>85pcs</b><br><b>100pcs ETA to WH 4/15</b><br><b>Dimmable</b> | 3900lm          | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4<br>Other: IP66 IK10 | -104°F to 140°F (- 40°C to +60°C) |
| Mars Series Jelly Jar <b>Class I, Division I</b>                                 |  | FME-MAR-4-A-I-P-ND-5Y-CGG<br><i>Clear Globe w/ Wire Guard</i>        | 40W     | <b>10pcs</b><br><b>4000K</b>                                    | 3900lm          | 4000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4<br>Other: IP66 IK10 | -104°F to 140°F (- 40°C to +60°C) |



TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

|                                                          |                                                                                     |                                                                                                                          |           |                                                     |         |       |      |                                                                                                                                                                                   |                                   |
|----------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|-----------|-----------------------------------------------------|---------|-------|------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|
| Mars Series Jelly Jar<br><b>Class I, Division I</b>      |     | FME-MAR-4-A-C-P-D-5Y-CGG<br><i>Clear Globe w/ Wire Guard</i>                                                             | 40W       | <b>Sold out<br/>Dimmable</b>                        | 3900lm  | 5000K | 120° | Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 | -104°F to 140°F (- 40°C to +60°C) |
| Universe Series Jelly Jar<br><b>Class I, Division II</b> |    | FME-UNI-2-A-C-ND-5Y-OPCM-CGG<br><i>Ceiling Surface Mount   Clear Globe with Wire Guard</i>                               | 20W       | <b>153pcs</b>                                       | 2800lm  | 5000K | 120° | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10                                | -104°F to 140°F (- 40°C to +60°C) |
| Universe Series Jelly Jar<br><b>Class I, Division II</b> |    | FME-UNI-3-A-C-ND-5Y-OPCM-CGG<br><i>Ceiling Surface Mount   Clear Globe with Wire Guard</i>                               | 30W (27W) | <b>8pcs</b>                                         | 4200lm  | 5000K | 120° | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10                                | -104°F to 140°F (- 40°C to +60°C) |
| Universe Series Jelly Jar<br><b>Class I, Division II</b> |    | FME-UNI-2-A-C-ND-5Y-P-CGG<br><i>Pendant Mount   Clear Globe with Wire Guard</i>                                          | 20W       | <b>123pcs</b>                                       | 2800lm  | 5000K | 120° | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK11                                | -104°F to 140°F (- 40°C to +60°C) |
| Universe Series Jelly Jar<br><b>Class I, Division II</b> |    | FME-UNI-3-A-C-ND-5Y-P-CGG<br><i>Pendant Mount   Clear Globe with Wire Guard</i><br>30W is being updated to 27W           | 30W (27W) | <b>Sold Out</b>                                     | 4200lm  | 5000K | 120° | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK11                                | -104°F to 140°F (- 40°C to +60°C) |
| Universe Series Jelly Jar<br><b>Class I, Division II</b> |    | FME-UNI-2-A-C-ND-5Y-OPWA-CGG<br><i>90 Degree Wall Mount   Clear Globe with Wire Guard</i>                                | 20W       | <b>10pcs</b>                                        | 2800lm  | 5000K | 120° | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10                                | -104°F to 140°F (- 40°C to +60°C) |
| Universe Series Jelly Jar<br><b>Class I, Division II</b> |    | FME-UNI-3-A-C-ND-5Y-OPWA-CGG<br><i>90 Degree Wall Mount   Clear Globe with Wire Guard</i><br>30W is being updated to 27W | 30W (27W) | <b>58pcs<br/>50pcs ETA to WH 4/15</b>               | 4200lm  | 5000K | 120° | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10                                | -104°F to 140°F (- 40°C to +60°C) |
| Pluto Series Linear<br><b>Class I, Division II</b>       |    | FME-PLU-2-2-LV-I-P-ND-5Y                                                                                                 | 20W       | <b>3pcs<br/>4000K</b>                               | 5400lm  | 4000K | 120° | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G IP66 IK10                                                                | -104°F to 140°F (-40°C to +60°C)  |
| Pluto Series Linear<br><b>Class I, Division II</b>       |   | FME-PLU-2-2-LV-C-P-ND-5Y                                                                                                 | 20W       | <b>15pcs</b>                                        | 5400lm  | 5000K | 120° | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G IP66 IK10                                                                | -104°F to 140°F (-40°C to +60°C)  |
| Pluto Series Linear<br><b>Class I, Division II</b>       |  | FME-PLU-2-4-LV-C-P-ND-5Y                                                                                                 | 40W       | <b>Sold Out<br/>50pcs ETA to WH 5/5</b>             | 5400lm  | 5000K | 120° | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G IP66 IK10                                                                | -104°F to 140°F (-40°C to +60°C)  |
| Pluto Series Linear<br><b>Class I, Division II</b>       |  | FME-PLU-4-4-LV-C-P-D-5Y                                                                                                  | 40W       | <b>290pcs<br/>Dimmable</b>                          | 5400 lm | 5000K | 120° | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G IP66 IK10                                                                | -104°F to 140°F (-40°C to +60°C)  |
| Pluto Series Linear<br><b>Class I, Division II</b>       |  | FME-PLU-4-4-LV-I-ND-5Y                                                                                                   | 40W       | <b>25pcs<br/>4000K</b>                              | 8100lm  | 4000K | 120° | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G IP66 IK10                                                                | -104°F to 140°F (-40°C to +60°C)  |
| Pluto Series Linear<br><b>Class I, Division II</b>       |  | FME-PLU-4-6-LV-I-P-ND-5Y                                                                                                 | 60W       | <b>83pcs<br/>4000K</b>                              | 8100lm  | 4000K | 120° | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G IP66 IK10                                                                | -104°F to 140°F (-40°C to +60°C)  |
| Pluto Series Linear<br><b>Class I, Division II</b>       |  | FME-PLU-4-6-LV-C-P-D-5Y                                                                                                  | 60W       | <b>53pcs<br/>100pcs ETA to BG 4/15<br/>Dimmable</b> | 8100lm  | 5000K | 120° | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G IP66 IK10                                                                | -104°F to 140°F (-40°C to +60°C)  |

TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

| Series                                             | Picture                                                                             | Model                                   | Wattage | Stock Available    | Lumens  | CCT   | Beam Angle | Ratings                                                                                                                                                                                                                                                            | Ambient Operation Temperature    |
|----------------------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------|---------|--------------------|---------|-------|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|
| Pluto Series Linear<br>Class I, Division II        |     | FME-PLU-4-8-LV-C-P-D-5Y                 | 80W     | 102pcs<br>Dimmable | 10800lm | 5000K | 120°       | Marine: UL 1598A, UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G, IP66 IK10                                                                                                                                                    | -104°F to 140°F (-40°C to +60°C) |
| Sun Series Linear<br>Class I, Division I           |    | FME-SUN-2-G-4-A-I-R-ND-5Y<br>Glass Lens | 40W     | 10pcs<br>4000K     | 5400lm  | 4000K | 120°       | Marine: UL 1598A, ABS<br>UL 844: Class I, Division I, Group C,D<br>Class I, Division II, Group A,B,C,D                                                                                                                                                             | -104°F to 140°F (-40°C to +60°C) |
| Sun Series Linear<br>Class I, Division I           |    | FME-SUN-2-G-4-A-C-R-ND-5Y<br>Glass Lens | 40W     | 23pcs              | 5400lm  | 5000K | 120°       | Marine: UL 1598A, ABS<br>UL 844: Class I, Division I, Group C,D<br>Class I, Division II, Group A,B,C,D                                                                                                                                                             | -104°F to 140°F (-40°C to +60°C) |
| Sun Series Linear<br>Class I, Division I           |    | FME-SUN-2-G-5-A-C-R-D-5Y<br>Glass Lens  | 50W     | 189pcs<br>Dimmable | 7000lm  | 5000K | 120°       | Marine: UL 1598A, ABS<br>UL 844: Class I, Division I, Group C,D<br>Class I, Division II, Group A,B,C,D                                                                                                                                                             | -104°F to 140°F (-40°C to +60°C) |
| Sun Series Linear<br>Class I, Division I           |    | FME-SUN-4-G-4-A-C-R-ND-5Y<br>Glass Lens | 40W     | Sold Out           | 5400lm  | 5000K | 120°       | Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 | -104°F to 140°F (-40°C to +60°C) |
| Sun Series Linear<br>Class I, Division I           |    | FME-SUN-4-G-4-A-C-R-D-5Y<br>Glass Lens  | 40W     | 110pcs<br>Dimmable | 5400lm  | 5000K | 120°       | Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 | -104°F to 140°F (-40°C to +60°C) |
| Sun Series Linear<br>Class I, Division I           |    | FME-SUN-4-G-6-A-I-R-D-5Y<br>Glass Lens  | 60W     | 110pcs<br>4000K    | 8100lm  | 4000K | 120°       | Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 | -104°F to 140°F (-40°C to +60°C) |
| Sun Series Linear<br>Class I, Division I           |    | FME-SUN-4-G-6-A-C-R-D-5Y<br>Glass Lens  | 60W     | 203pcs<br>Dimmable | 8100lm  | 5000K | 120°       | Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 | -104°F to 140°F (-40°C to +60°C) |
| Sun Series Linear<br>Class I, Division I           |    | FME-SUN-4-G-8-A-C-R-ND-5Y<br>Glass Lens | 80W     | Sold Out           | 10800lm | 5000K | 120°       | Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 | -104°F to 140°F (-40°C to +60°C) |
| Sun Series Linear<br>Class I, Division I           |   | FME-SUN-4-G-8-A-I-R-ND-5Y<br>Glass Lens | 80W     | 73pcs<br>4000K     | 10800lm | 4000K | 120°       | Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 | -104°F to 140°F (-40°C to +60°C) |
| Sun Series Linear<br>Class I, Division I           |  | FME-SUN-4-G-8-A-C-R-D-5Y<br>Glass Lens  | 80W     | 33pcs<br>Dimmable  | 10800lm | 5000K | 120°       | Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 | -104°F to 140°F (-40°C to +60°C) |
| Sun Series Linear<br>Class I, Division I           |  | FME-SUN-4-G-10-A-C-R-D-5Y<br>Glass Lens | 100W    | 63pcs<br>Dimmable  | 13500lm | 5000K | 120°       | Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 | -104°F to 104°F                  |
| Meridian Series<br>Vaportight Class I, Division II |  | FME-MID-24-3-A-C-P-D-SM-5Y<br>2FT       | 30W     | 230pcs<br>Dimmable | 4050lm  | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10                                                                                                                 | -104°F to 113°F (-40°C to +45°C) |
| Meridian Series<br>Vaportight Class I, Division II |  | FME-MID-24-3-A-I-P-D-SM-5Y<br>2FT       | 30W     | 5pcs<br>4000K      | 4050lm  | 4000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10                                                                                                                 | -104°F to 113°F (-40°C to +45°C) |

TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

| Series                                                                            | Picture                                                                             | Model                                                         | Wattage | Stock Available                                                 | Lumens  | CCT   | Beam Angle | Ratings                                                                                                                                                                          | Ambient Operation Temperature                                                              |
|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------|---------|-----------------------------------------------------------------|---------|-------|------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|
| Meridian Series<br>Vaportight <b>Class I, Division II</b>                         |     | FME-MID-24-4-A-C-P-D-SM-5Y<br>2FT                             | 40W     | <b>150pcs</b><br><b>Dimmable</b>                                | 5400lm  | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10                               | -104°F to 113°F (- 40°C to +45°C)                                                          |
| Meridian Series<br>Vaportight <b>Class I, Division II</b>                         |    | FME-MID-48-5-A-I-P-ND-SM-5Y<br>4FT                            | 50W     | <b>150pcs</b><br><b>4000K</b>                                   | 6750lm  | 4000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10                               | -104°F to 113°F (- 40°C to +45°C)                                                          |
| Meridian Series<br>Vaportight <b>Class I, Division II</b>                         |    | FME-MID-48-5-A-C-P-D-SM-5Y<br>4FT                             | 50W     | <b>150pcs</b><br><b>Dimmable</b>                                | 6750lm  | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10                               | -104°F to 113°F (- 40°C to +45°C)                                                          |
| Meridian Series<br>Vaportight <b>Class I, Division II</b>                         |    | FME-MID-48-6-A-C-P-D-SM-5Y<br>4FT                             | 60W     | <b>70pcs</b><br><b>Dimmable</b>                                 | 6750lm  | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10                               | -104°F to 113°F (- 40°C to +45°C)                                                          |
| Meridian-R Series<br>Hazardous location & NSF Rated   <b>Class I, Division II</b> |    | MID-R-24-3-1-C-P-D<br>2FT   304 Stainless steel   White   NSF | 30W     | <b>87pcs</b><br><b>Dimmable</b>                                 | 4050lm  | 5000K | 120°       | NSF-Rated Optional Marine:UL 1598A,ABS UL 844: Class I, DivisionII, GroupA,B,C,D ClassII, DivisionI & II, Group E,F,G ClassIII Temp.Code: T3 Other:IP66 IK10                     | -40°C to +40°C (T6) -40°C to +60°C (T5)                                                    |
| Meridian-R Series<br>Hazardous location & NSF Rated   <b>Class I, Division II</b> |    | MID-R-48-5-A-C-P-D<br>4FT   304 Stainless steel   White   NSF | 50W     | <b>58pcs</b><br><b>Dimmable</b>                                 | 6750lm  | 5000K | 120°       | NSF-Rated Optional Marine:UL 1598A,ABS UL 844: Class I, DivisionII, GroupA,B,C,D ClassII, DivisionI & II, Group E,F,G ClassIII Temp.Code: T3 Other:IP66 IK10                     | -40°C to +40°C (T6) -40°C to +60°C (T5)                                                    |
| XF Linear Light<br><b>Class I, Division II</b>                                    |    | XF-2-4-C-D-Z-WM<br>2FT                                        | 40W     | <b>40pcs</b><br><b>Dimmable</b>                                 | 5600lm  | 5000K | 120°       | Marine:UL 1598A,ABS UL 844: Class I, DivisionII, GroupA,B,C,D ClassII, DivisionI & II, Group E,F,G ClassIII Temp.Code: T5/T4 Other:IP66 IK10                                     | T5(-40°C to +40°C) T4(-40°C to +55°C)                                                      |
| XF Linear Light<br><b>Class I, Division II</b>                                    |    | XF-4-6-C-D-Z-WM<br>4FT                                        | 60W     | <b>27pcs</b><br><b>100pcs ETA to WH 4/15</b><br><b>Dimmable</b> | 8400lm  | 5000K | 120°       | Marine:UL 1598A,ABS UL 844: Class I, DivisionII, GroupA,B,C,D ClassII, DivisionI & II, Group E,F,G ClassIII Temp.Code: T5/T4 Other:IP66 IK10                                     | T5(-40°C to +40°C) T4(-40°C to +55°C)                                                      |
| XF Linear Light<br><b>Class I, Division II</b>                                    |    | XF-4-8-C-D-Z-WM<br>4FT                                        | 80W     | <b>145pcs</b><br><b>Dimmable</b>                                | 10800lm | 5000K | 120°       | Marine:UL 1598A,ABS UL 844: Class I, DivisionII, GroupA,B,C,D ClassII, DivisionI & II, Group E,F,G ClassIII Temp.Code: T5/T4 Other:IP66 IK10                                     | T5(-40°C to +40°C) T4(-40°C to +55°C)                                                      |
| LFL Series, Flood/Area Light <b>Class I, Division II</b>                          |  | LFL-1-E-LV1-C-Z-TM                                            | 200W    | <b>190pcs</b>                                                   | 2600lm  | 5000K | 120°       | Marine:UL 1598A,ABS UL 844: Class I, DivisionII, GroupA,B,C,D ClassII, DivisionI & II, Group E,F,G ClassIII                                                                      | - 104°F to 131°F (-40°C to +55°C)                                                          |
| LFL Series, Flood/Area Light <b>Class I, Division II</b>                          |  | LFL-2-D-LV1-C-Z-TM                                            | 150W    | <b>43pcs</b>                                                    | 19500lm | 5000K | 120°       | Temp.Code: T4(LFL2),T3(LFL1) Other:IP66 IK10                                                                                                                                     | - 104°F to 131°F (-40°C to +55°C)                                                          |
| LFL Series, Flood/Area Light <b>Class I, Division II</b>                          |  | LFL-2-C-LV1-C-Z-TM                                            | 100W    | <b>52pcs</b>                                                    | 13500lm | 5000K | 120°       | Temp.Code: T4(LFL2),T3(LFL1) Other:IP66 IK10                                                                                                                                     | - 104°F to 131°F (-40°C to +55°C)                                                          |
| ZTP Series Exit Light<br><b>Class I, Division I</b>                               |  | ZTP-5-RD-LV<br>Double-Faced with Red Letters & White Panel    | 5W      | <b>210pcs</b>                                                   | 650lm   | 5000K | 120°       | Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II,Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 | -104°F to 140°F (- 40°C to +60°C                                                           |
| LUMIX-G Series (LGE)<br>Exit Light <b>Class I, Division II</b>                    |  | LGE-5-LV-G-WM<br>Green Leds                                   | 5W      | <b>15pcs</b>                                                    | 300lm   | 5000K | 120°       | Marine:UL 1598A,ABS UL 844: Class I, DivisionII, GroupA,B,C,D ClassII, DivisionI & II, Group E,F,G ClassIII Temp.Code: T5/T4 Other:IP66 IK10                                     | Ta= 0°C to + 45°C, when batteryis charged;<br>Ta= -10°C to + 60°C, when battery discharges |

TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

Accessories 13 to 23 are compatible with all series with the exception of the LIH, NEB, SOL & ROC

FME LIGHTING | 877-234-8460 | info@fmelighting.com

Inventory Levels as of 3/27/2025

## ACCESSORIES

| Picture                                                                             | Model                 | Stock Available | Description                                                                                              |
|-------------------------------------------------------------------------------------|-----------------------|-----------------|----------------------------------------------------------------------------------------------------------|
|    | SOL-CM                | 21pcs           | Ceiling Mount Bracket for <b>Solstice Series</b><br>4x 3/4"NPT Cable Entries, 3 sealed by blanking plugs |
|    | SOL-WM                | 43pcs           | Wall Mount Bracket for <b>Solstice Series</b><br>4x 3/4"NPT Cable Entries, 3 sealed by blanking plugs    |
|    | NEB-CM                | 24pcs           | Ceiling Mount Bracket for <b>Nebula Series</b><br>4x 3/4"NPT Cable Entries, 3 sealed by blanking plugs   |
|    | NEB-WM                | 51pcs           | Wall Mount Bracket for <b>Nebula Series</b><br>4x 3/4"NPT Cable Entries, 3 sealed by blanking plugs      |
|    | ROC-PLM               | 50pcs           | <b>Rocket Series</b> Pole Adaptor                                                                        |
|    | 1- Meter Safety Chain | 100pcs          | 1- Meter Safety Chain                                                                                    |
|   | Slip Fitter           | 180pcs          | Slip Fitter                                                                                              |
|  | OPEB                  | 183pcs          | JUNCTION BOX <b>C1,D1</b>                                                                                |
|  | FME-MID-PM            | 90sets          | Mounting Pole & Clamp<br>for Meridian (MID) Series fixtures                                              |
|  | OPWA25                | 100pcs          | <b>C1, D1</b>   25 DEGREE WALL MOUNT                                                                     |
|  | OPWA90                | 235pcs          | <b>C1, D1</b>   90 DEGREE WALL MOUNT &<br>JUNCTION Box                                                   |
|  | OPPS25                | 310pcs          | 25 DEGREE POLE MOUNT                                                                                     |

### TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

| Picture                                                                           | Model   | Stock Available | Description                  |
|-----------------------------------------------------------------------------------|---------|-----------------|------------------------------|
|  | OPPS90  | 145pcs          | 90 DEGREE POLE MOUNT         |
|  | OPWA    | 224pcs          | 90 DEGREE WALL MOUNT         |
|  | NIP-3/4 | 500pcs          | 3/4" THREADED CONDUIT NIPPLE |
|  | HOOK-1  | 105pcs          | 3/4" HOOK                    |