


STOCK ONLY Hazardous Location / Explosion-Proof: USA Inventory - Tariff-Free



Inventory Levels as of Aug, 6, 2025

FME LIGHTING | 877-234-8460 | info@fmelighting.com

REP PRICING FIRM UNTIL: Q3 2025

Series	Picture	Model	Wattage	Stock Available	Lumens	CCT	Beam Angle	Ratings	Ambient Operation Temperature
Solstice Series Area / Low-High Bay Class I, Division I		SOL-5-LV-C-120-7-NPT-TR/PM-5Y-S <i>Pendant +Trunion 1x 3/4" without exposed power cord 100-277VAC</i>	50W	72pcs	7000lm (140LM/W)	5000K Ra70	120° (No Lens)	NEMA 4X UL 1598, UL 1598A, UL 8750, UL 844 CSA C22.2 No. 137, CSA C22.2 No. 250.0 Temp. Code: T5,T6	-40°C to + 65°C
Solstice Series Area / Low-High Bay Class I, Division I		SOL-7-LV-C-120-7-NPT-TR/PM-5Y-S <i>Pendant +Trunion 1x 3/4" without exposed power cord 100-277VAC</i>	70W	28pcs	9800lm (140LM/W)	5000K Ra70	120° (No Lens)	NEMA 4X UL 1598, UL 1598A, UL 8750, UL 844 CSA C22.2 No. 137, CSA C22.2 No. 250.0 Temp. Code: T5,T6	-40°C to + 65°C -40°C to + 60°C
Rocket Series Flood Light Class I, Division II		ROC-24-LV-C-TYPEV-XP-5Y-S <i>Trunion 2x 3/4" without exposed power cord 100-277VAC</i>	240W	128pcs	36,000lm	5000K Ra70	120° (No Lens)	NEMA 4X UL 1598, UL 1598A, UL 8750, UL 844 CSA C22.2 No. 137, CSA C22.2 No. 250.0 Temp. Code: T5,T6	-40°C to 50°C (-40°F to 122°F)
Nebula Series Low-High Bay Class I, Division II		NEB-10-LV-C-TYPEV-70CRI-NPT-TR/PM-5Y-S <i>Pendant +Trunion 1x 3/4" without exposed power cord 100-277VAC</i>	100W	198pcs Dimmable	10125lm	5000K Ra70	120° (No Lens)	NEMA 4X UL 1598, UL 1598A, UL 8750, UL 844, UL924 CSA C22.2 No. 137, CSA C22.2 No. 250.0 CSA C22.2 No. 141 Temp. Code: T5,T6	-40° to +60°C MAX: -40°C to 65°C
Nebula Series Low-High Bay Class I, Division II		NEB-15-LV-C-TYPEV-70CRI-NPT-TR/PM-5Y-S <i>Pendant +Trunion 1x 3/4" without exposed power cord 100-277VAC</i>	150W	340pcs Dimmable	20250lm	5000K Ra70	120° (No Lens)	NEMA 4X UL 1598, UL 1598A, UL 8750, UL 844, UL924 CSA C22.2 No. 137, CSA C22.2 No. 250.0 CSA C22.2 No. 141 Temp. Code: T5,T6	-40° to +55° MAX: -40°C to 65°C
Nebula Series Low-High Bay Class I, Division II		NEB-24-LV-C-TYPEV-70CRI-NPT-TR/PM-5Y-S <i>Pendant +Trunion 1x 3/4" without exposed power cord 100-277VAC</i>	240W	218pcs Dimmable	32400lm	5000K Ra70	120° (No Lens)	NEMA 4X UL 1598, UL 1598A, UL 8750, UL 844, UL924 CSA C22.2 No. 137, CSA C22.2 No. 250.0 CSA C22.2 No. 141 Temp. Code: T5,T6	-40°C to +45°C MAX: -40°C to 65°C
LIH Series Linear Light Class I, Division II		LIH-5-LV-50-D-DL-B-TM/PM-3/4-S <i>Pendant +Trunion 1x 3/4" without exposed power cord 100-277VAC</i>	50W	53pcs Dimmable	8000lm (160LM/W)	5000K Ra70	Diffused Cover	NEMA 4X UL 844, UL:50/E,UL 1598/A, UL 8750, UL924 CSA C22.2 No. 137, CSA C22.2 No. 250.0 CSA C22.2 No. 141, C22.2 No. 94.1, C22.2 No.94.2	-40°C to + 45°C (-40°F to +113°F)
LIH Series Linear Light Class I, Division II		LIH-10-LV-50-D-DL-B-TM/PM-3/4-S <i>Pendant +Trunion 1x 3/4" without exposed power cord 100-277VAC</i>	100W	15pcs Dimmable	16000lm (160LM/W)	5000K Ra70	Diffused Cover	NEMA 4X UL 844, UL:50/E,UL 1598/A, UL 8750, UL924 CSA C22.2 No. 137, CSA C22.2 No. 250.0 CSA C22.2 No. 141, C22.2 No. 94.1, C22.2 No.94.2	-40°C to + 40°C (-40°F to +104°F)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-4-A-C-P-ND <i>Glass Lens</i>	40W	50pcs	5400lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-6-A-C-P-ND <i>Glass Lens</i>	60W	Sold Out	8100lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-6-A-C-P-D <i>Glass Lens</i>	60W	Sold Out Dimmable	8100lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-6L-A-C-P-ND <i>Glass Lens 6L (60W) = 12.5x9.45x6.5in</i>	60W	100pcs	8100lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-6L-B-I-P-D <i>Glass Lens 6L (60W) = 12.5x9.45x6.5in</i>	60W	50pcs 4000K	8100lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)

TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

FME Lighting | 877 - 234 - 8460 | info@fmelighting.com | 1

Series	Picture	Model	Wattage	Stock Available	Lumens	CCT	Beam Angle	Ratings	Ambient Operation Temperature
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-6L-B-C-P-D <i>Glass Lens</i> 6L (60W) = 12.5x9.45x6.5in	60W	30pcs 200-480V	8100lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-8-A-I-P-ND <i>Glass Lens</i>	80W	150pcs 4000K	8100lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-8-A-C-P-D <i>Glass Lens</i>	80W	130pcs Dimmable	10400lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX G-10-A-C-P-D <i>Glass Lens</i>	100W	400pcs Dimmable	13500lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX G-10-A-I-P-ND <i>Glass Lens</i>	100W	45pcs 4000K	13500lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-10-B-C-P-D <i>Glass Lens</i>	100W	65pcs DIM 200-480V	13500 lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-15-A-C-P-ND <i>Glass Lens</i>	150W	Sold Out	20250lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-15-A-C-P-D <i>Glass Lens</i>	150W	10pcs 87pcs ETA to WH 9/10 Dimmable	20250lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-15-B-C-P-D <i>Glass Lens</i>	150W	Sold Out 50pcs ETA to WH 8/20 200-480V	20250lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-20-A-C-P-ND <i>Glass Lens</i>	200W	Sold Out	28000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-20-A-C-P-D <i>Glass Lens</i>	200W	25pcs 4000K	28000lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-20-A-C-P-D <i>Glass Lens</i>	200W	800pcs Dimmable	28000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-25-A-C-P-D <i>Glass Lens</i>	250W	80pcs Dimmable	35,000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)




TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

Series	Picture	Model	Wattage	Stock Available	Lumens	CCT	Beam Angle	Ratings	Ambient Operation Temperature
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-30-A-C-P-D <i>Glass Lens</i>	300W	80pcs Dimmable	42000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX G-40-A-C-P-D <i>Glass Lens</i>	400W	75pcs Dimmable	56000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Moon Series Highbay Class I, Division II		FME-M00-4-A-I-ND-5Y	40W	Sold Out 4000K	8100 lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3	-104°F to 122°F (- 40°C to +50°C)
Moon Series Highbay Class I, Division II		FME-M00-6-A-C-P-ND-5Y	60W	Sold Out	8100lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3	-104°F to 122°F (- 40°C to +50°C)
Moon Series Highbay Class I, Division II		FME-M00-6-A-C-P-D-5Y	60W	40pcs Dimmable	8100lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3	-104°F to 122°F (- 40°C to +50°C)
Moon Series Highbay Class I, Division II		FME-M00-6L-A-C-P-D-5Y	60W	125pcs Dimmable	8100lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +50°C)
Moon Series Highbay Class I, Division II		FME-M00-6-A-C-P-D-5Y	60W	Sold Out	8100lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +50°C)
Moon Series Highbay Class I, Division II		FME-M00-8-A-C-P-ND-5Y	80W	Sold Out	10800lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +50°C)
Moon Series Highbay Class I, Division II		FME-M00-8-A-I-P-D-5Y	80W	45pcs Dimmable 4000K	10800lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +50°C)
Moon Series Highbay Class I, Division II		FME-M00-8-A-C-P-D-5Y	80W	1200pcs Dimmable	10800lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +50°C)
Moon Series Highbay Class I, Division II		FME-M00-10- A-C-P-ND-5Y	100W	Sold Out	14000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)
Moon Series Highbay Class I, Division II		FME-M00-10- A-C-P-D-5Y	100W	140pcs Dimmable	14000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)
Moon Series Highbay Class I, Division II		FME-M00-15-A-C-P-ND-5Y	150W	Sold Out	21000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)




TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

Series	Picture	Model	Wattage	Stock Available	Lumens	CCT	Beam Angle	Ratings	Ambient Operation Temperature
Moon Series Highbay Class I, Division II		FME-MOO-15-A-I-P-D-5Y	150W	15pcs Dimmable 4000K	21000lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)
Moon Series Highbay Class I, Division II		FME-MOO-15-A-C-P-D-5Y	150W	140pcs Dimmable	21000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)
Moon Series Highbay Class I, Division II		FME-MOO-15-B-C-P-D-5Y	150W	30pcs Dimmable 200-480V	21000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)
Moon Series Highbay Class I, Division II		FME-MOO-20-B-C-P-ND-5Y	200W	Sold Out	28000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)
Moon Series Highbay Class I, Division II		FME-MOO-20-A-I-P-ND-5Y	200W	95pcs 4000K	28000lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)
Moon Series Highbay Class I, Division II		FME-MOO-20-A-C-P-D-5Y	200W	120pcs Dimmable	28000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)
Moon Series Highbay Class I, Division II		FME-MOO-20-B-C-P-D-5Y	200W	50pcs Dimmable 200-480V	28000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)
Moon Series Highbay Class I, Division II		FME-MOO-25-A-C-P-D-5	250W	15pcs Dimmable	33750lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)
Moon Series Highbay Class I, Division II		FME-MOO-30-A-C-P-D-5Y	300W	40pcs Dimmable	42000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)
Moon Series Highbay Class I, Division II		FME-MOO-40-A-C-P-D-5Y	400W	Sold Out Dimmable	56000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)
Star Series Highbay Class I, Division I		FME-STA-4-42-A-C-R-D-5Y	40W	Sold Out Dimmable	5400lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II,Group E,F,G ClassIII Temp. Code: T4 Other: IP66 IK1	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-6-42-A-I-R-ND-5Y	60W	Sold Out 4000K	8400lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II,Group E,F,G ClassIII Temp. Code: T4 Other: IP66 IK1	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-6-42-A-C-R-D-5Y	60W	1800pcs Dimmable	8400lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II,Group E,F,G ClassIII Temp. Code: T4 Other: IP66 IK1	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)

TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

Series	Picture	Model	Wattage	Stock Available	Lumens	CCT	Beam Angle	Ratings	Ambient Operation Temperature
Star Series Highbay Class I, Division I		FME-STA-8-42-A-I-R-ND-5Y	80W	50pcs 4000K	11200lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK1	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-8-42-A-C-R-D-5Y	80W	70pcs Dimmable	11200lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK1	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-10-42-A-C-R-ND-5Y	100W	Sold Out	13500lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-10-42-A-I-R-ND-5Y	100W	45pcs 4000K	13500lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-10-42-A-C-R-D-5Y	100W	110pcs Dimmable	13500lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-15-42-B-I-R-D-5Y	150W	10pcs Dimmable 200-480V	20250lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-15-42-A-C-R-D-5Y	150W	40pcs 200pcs ETA to WH 9/10 Dimmable	20250lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-15-42-A-I-R-ND-5Y	150W	10pcs 4000K	20250lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-20-42-A-I-R-ND-5Y	200W	Sold Out 4000K	27000 lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-20-42-A-I-R-D-5Y	200W	Sold Out 30pcs ETA to WH 8/20 Dimmable	27000 lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-20-42-B-C-R-D-5Y	200W	Sold Out Dimmable 200-480V	27000 lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-10-42-A-C-R-D-5Y-OPGG <i>with Frosted Globe & Guard</i>	100W	20pcs Dimmable	13500lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-24-42-A-C-R-D-5Y	240W	Sold Out Dimmable	32400 lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)

TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

Series	Picture	Model	Wattage	Stock Available	Lumens	CCT	Beam Angle	Ratings	Ambient Operation Temperature
Star Series Highbay Class I, Division I		FME-STA-25-42-A-C-R-D-5Y	250W	50pcs Dimmable	35000lm	5000K	120°	Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Earth Series Flood Light/High Bay Class I, Division I		FME-EAT-G-6-A-C-P-ND-5Y Glass Lens	60W	45pcs	8100lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	104°F to 131°F (-40°C to +55°C)
Earth Series Flood Light/High Bay Class I, Division I		FME-EAT-G-6-A-I-P-ND-5Y Glass Lens	80W	10pcs 4000K	8100lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	104°F to 131°F (-40°C to +55°C)
Earth Series Flood Light/High Bay Class I, Division I		FME-EAT-G-8-A-C-P-D-5Y Glass Lens	80W	10pcs Dimmable	11200lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 131°F (-40°C to +55°C)
Earth Series Flood Light/High Bay Class I, Division I		FME-EAT-G-10-A-C-P-ND-5Y Glass Lens	100W	Sold Out	13500lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 131°F (-40°C to +55°C)
Earth Series Flood Light/High Bay Class I, Division I		FME-EAT-G-10-A-C-P-D-5 Glass Lens	100W	67pcs Dimmable	13500lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 131°F (-40°C to +55°C)
Earth Series Flood Light/High Bay Class I, Division I		FME-EAT-G-10-A-I-P-ND-5 Glass Lens	150W	28pcs 4000K	20250lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 131°F (-40°C to +55°C)
Earth Series Flood Light/High Bay Class I, Division I		FME-EAT-G-15-A-C-P-D-5Y Glass Lens	150W	Sold Out 40pcs ETA to WH 9/10 Dimmable	20250lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 131°F (-40°C to +55°C)
Earth Series Flood Light/High Bay Class I, Division I		FME-EAT-G-15-B-C-P-ND-5Y Glass Lens	150W	50pcs 200-480V	20250lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 131°F (-40°C to +55°C)
MRT Series Maritron Flanged Ceiling Surface Mount, Class I, Division II		MRT-B-4-LV1-C-D-CM Includes 1 Meter Chains and Lift rings	40W	28pcs Dimmable	5200lm 1X4	5000K	120°	Marine: UL 1598, UL844, UL924 UL 844: Class I, Division II, Group A,B,C, D Temp. Code: T4 Other: IP66 IK10	-40°C to 60°C
MRT Series Maritron Flanged Ceiling Surface Mount, Class I, Division II		MRT-C-4-LV1-C-D-CM Includes 1 Meter Chains and Lift rings	40W	43pcs Dimmable	5200lm 2X2	5000K	120°	Marine: UL 1598, UL844, UL924 UL 844: Class I, Division II, Group A,B,C, D Temp. Code: T4 Other: IP66 IK10	-40°C to 60°C
MRT Series Maritron Flanged Ceiling Surface Mount, Class I, Division II		MRT-D-6-LV1-C-D-CM Includes 1 Meter Chains and Lift rings	60W	20pcs Dimmable	7800lm 2X4	5000K	120°	Marine: UL 1598, UL844, UL924 UL 844: Class I, Division II, Group A,B,C, D Temp. Code: T4 Other: IP66 IK10	-40°C to 60°C
MRT Series Maritron Flanged Ceiling Surface Mount, Class I, Division II		MRT-D-10-LV1-C-D-CM Includes 1 Meter Chains and Lift rings	100W	5pcs Dimmable	14000 lm 2X4	5000K	120°	Marine: UL 1598, UL844, UL924 UL 844: Class I, Division II, Group A,B,C, D Temp. Code: T4 Other: IP66 IK10	-40°C to 60°C

TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

Series	Picture	Model	Wattage	Stock Available	Lumens	CCT	Beam Angle	Ratings	Ambient Operation Temperature
Nova Series Coming Soon, Class I, Division II		Coming Soon <i>Trunnion mount</i>	80W	87pcs Dimmable	10800lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D ClassII, Division I & II, Group E,F,G ClassIII Temp. Code: T5/T4 Other: IP66 IK10	-104°F to 122°F (-40°C to +40°C)
Mercury Series Highbay Class I, Division I		FME-MER-10-A-I-R-ND-5Y	100W	42pcs	13500lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II,Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Mercury Series Highbay Class I, Division I		FME-MER-15-A-I-R-ND-5Y	150W	8pcs	20250lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II,Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Mars Series Jelly Jar Class I, Division I		FME-MAR-2-A-C-ND-5Y-CGG <i>Clear Globe w/ Wire Guard</i>	20W	80pcs	2700lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II,Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Mars Series Jelly Jar Class I, Division I		FME-MAR-3-A-C-P-ND-5Y-CGG <i>Clear Globe w/ Wire Guard</i>	30W	Sold Out	4050 lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II,Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Mars Series Jelly Jar Class I, Division I		FME-MAR-3-A-C-P-D-5Y-CGG <i>Clear Globe w/ Wire Guard</i>	30W	30pcs Dimmable	3900lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II,Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Mars Series Jelly Jar Class I, Division I		FME-MAR-4-A-I-P-ND-5Y-CGG <i>Clear Globe w/ Wire Guard</i>	40W	Sold Out 4000K	3900lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II,Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Mars Series Jelly Jar Class I, Division I		FME-MAR-4-A-C-P-D-5Y-CGG <i>Clear Globe w/ Wire Guard</i>	40W	Sold Out 120pcs ETA to WH 9/5 Dimmable	3900lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II,Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Universe Series Jelly Jar Class I, Division II		FME-UNI-2-A-C-ND-5Y-OPCM-CGG <i>Ceiling Surface Mount Clear Globe with Wire Guard</i>	20W	Sold Out 98pcs ETA to WH 8/20	2800lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Universe Series Jelly Jar Class I, Division II		FME-UNI-3-A-C-ND-5Y-OPCM-CGG <i>Ceiling Surface Mount Clear Globe with Wire Guard</i>	27W	90pcs	4200lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Universe Series Jelly Jar Class I, Division II		FME-UNI-2-A-C-ND-5Y-P-CGG <i>Pedant Mount Clear Globe with Wire Guard</i>	20W	10pcs	2800lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK11	-104°F to 140°F (- 40°C to +60°C)
Universe Series Jelly Jar Class I, Division II		FME-UNI-3-A-C-ND-5Y-P-CGG <i>Pedant Mount Clear Globe with Wire Guard</i> 30W is being updated to 27W	30W (27W)	Sold Out	4200lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK11	-104°F to 140°F (- 40°C to +60°C)
Universe Series Jelly Jar Class I, Division II		FME-UNI-2-A-C-ND-5Y-OPWA-CGG <i>90 Degree Wall Mount Clear Globe with Wire Guard</i>	20W	85pcs	2800lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)

TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

Series	Picture	Model	Wattage	Stock Available	Lumens	CCT	Beam Angle	Ratings	Ambient Operation Temperature
Universe Series Jelly Jar Class I, Division II		FME-UNI-3-A-C-ND-5Y-OPWA-CGG 90 Degree Wall Mount Clear Globe with Wire Guard 30W is being updated to 27W	27W	Sold Out 150pcs ETA to WH 9/15	4200lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (-40°C to +60°C)
Pluto Series Linear Class I, Division II		FME-PLU-2-2-LV-I-P-ND-5Y	20W	Sold Out 4000K	5400lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G IP66 IK10	-104°F to 140°F (-40°C to +60°C)
Pluto Series Linear Class I, Division II		FME-PLU-2-2-LV-C-P-ND-5Y	20W	15pcs	5400lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G IP66 IK10	-104°F to 140°F (-40°C to +60°C)
Pluto Series Linear Class I, Division II		FME-PLU-2-4-LV-C-P-ND-5Y	40W	50pcs	5400lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G IP66 IK10	-104°F to 140°F (-40°C to +60°C)
Pluto Series Linear Class I, Division II		FME-PLU-4-4-LV-C-P-D-5Y	40W	190pcs Dimmable	5400 lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G IP66 IK10	-104°F to 140°F (-40°C to +60°C)
Pluto Series Linear Class I, Division II		FME-PLU-4-4-LV-I-ND-5Y	40W	25pcs 4000K	8100lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G IP66 IK10	-104°F to 140°F (-40°C to +60°C)
Pluto Series Linear Class I, Division II		FME-PLU-4-6-LV-I-P-ND-5Y	60W	50pcs 4000K	8100lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G IP66 IK10	-104°F to 140°F (-40°C to +60°C)
Pluto Series Linear Class I, Division II		FME-PLU-4-6-LV-C-P-D-5Y	60W	90pcs Dimmable	8100lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G IP66 IK10	-104°F to 140°F (-40°C to +60°C)
Pluto Series Linear Class I, Division II		FME-PLU-4-8-LV-C-P-D-5Y	80W	8pcs 49pcs ETA to WH 9/10 Dimmable	10800lm	5000K	120°	Marine: UL 1598A, UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G, IP66 IK10	-104°F to 140°F (-40°C to +60°C)
Sun Series Linear Class I, Division I		FME-SUN-2-G-4-A-I-R-ND-5Y Glass Lens	40W	5pcs 4000K	5400lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D	-104°F to 140°F (-40°C to +60°C)
Sun Series Linear Class I, Division I		FME-SUN-2-G-4-A-C-R-ND-5Y Glass Lens	40W	15pcs	5400lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D	-104°F to 140°F (-40°C to +60°C)
Sun Series Linear Class I, Division I		FME-SUN-2-G-5-A-C-R-D-5Y Glass Lens	50W	80pcs Dimmable	7000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D	-104°F to 140°F (-40°C to +60°C)
Sun Series Linear Class I, Division I		FME-SUN-4-G-4-A-C-R-ND-5Y Glass Lens	40W	Sold Out	5400lm	5000K	120°	Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (-40°C to +60°C)


TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

Series	Picture	Model	Wattage	Stock Available	Lumens	CCT	Beam Angle	Ratings	Ambient Operation Temperature
Sun Series Linear Class I, Division I		FME-SUN-4-G-4-A-C-R-D-5Y Glass Lens	40W	75pcs Dimmable	5400lm	5000K	120°	Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Sun Series Linear Class I, Division I		FME-SUN-4-G-6-A-I-R-D-5Y Glass Lens	60W	40pcs 4000K	8100lm	4000K	120°	Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Sun Series Linear Class I, Division I		FME-SUN-4-G-6-A-C-R-D-5Y Glass Lens	60W	120pcs Dimmable	8100lm	5000K	120°	Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Sun Series Linear Class I, Division I		FME-SUN-4-G-8-A-C-R-ND-5Y Glass Lens	80W	Sold Out	10800lm	5000K	120°	Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Sun Series Linear Class I, Division I		FME-SUN-4-G-8-A-I-R-ND-5Y Glass Lens	80W	40pcs 4000K	10800lm	4000K	120°	Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Sun Series Linear Class I, Division I		FME-SUN-4-G-8-A-C-R-D-5Y Glass Lens	80W	50pcs Dimmable	10800lm	5000K	120°	Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Sun Series Linear Class I, Division I		FME-SUN-4-G-10-A-C-R-D-5Y Glass Lens	100W	Sold Out Dimmable	13500lm	5000K	120°	Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 104°F
Meridian Series Vaportight Class I, Division II		FME-MID-24-3-A-C-P-D-SM-5Y 2FT	30W	230pcs Dimmable	4050lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 113°F (- 40°C to +45°C)
Meridian Series Vaportight Class I, Division II		FME-MID-24-3-A-I-P-D-SM-5Y 2FT	30W	Sold Out 4000K	4050lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 113°F (- 40°C to +45°C)
Meridian Series Vaportight Class I, Division II		FME-MID-24-4-A-C-P-D-SM-5Y 2FT	40W	Sold Out Dimmable	5400lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 113°F (- 40°C to +45°C)
Meridian Series Vaportight Class I, Division II		FME-MID-48-5-A-I-P-ND-SM-5Y 4FT	50W	170pcs 4000K	6750lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 113°F (- 40°C to +45°C)
Meridian Series Vaportight Class I, Division II		FME-MID-48-5-A-C-P-D-SM-5Y 4FT	50W	85pcs Dimmable	6750lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 113°F (- 40°C to +45°C)
Meridian Series Vaportight Class I, Division II		FME-MID-48-6-A-C-P-D-SM-5Y 4FT	60W	55pcs Dimmable	6750lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 113°F (- 40°C to +45°C)

TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

Series	Picture	Model	Wattage	Stock Available	Lumens	CCT	Beam Angle	Ratings	Ambient Operation Temperature
Meridian-R Series Hazardous location & NSF Rated Class I, Division II		MID-R-24-3-1-C-P-D 2FT Non-Metallic White NSF	30W	80pcs Dimmable	4050lm	5000K	120°	NSF-Rated Optional Marine:UL 1598A,ABS UL 844: Class I, DivisionII, GroupA,B,C,D ClassII, DivisionI & II, Group E,F,G ClassIII Temp.Code: T3 Other:IP66 IK10	-40°C to +40°C (T6) -40°C to +60°C (T5)
Meridian-R Series Hazardous location & NSF Rated Class I, Division II		MID-R-48-5-A-C-P-D 4FT Non-Metallic White NSF	50W	110pcs Dimmable	6750lm	5000K	120°	NSF-Rated Optional Marine:UL 1598A,ABS UL 844: Class I, DivisionII, GroupA,B,C,D ClassII, DivisionI & II, Group E,F,G ClassIII Temp.Code: T3 Other:IP66 IK10	-40°C to +40°C (T6) -40°C to +60°C (T5)
XF Linear Light Class I, Division II		XF-2-4-C-D-Z-WM 2FT	40W	80pcs Dimmable	5600lm	5000K	120°	Marine:UL 1598A,ABS UL 844: Class I, DivisionII, GroupA,B,C,D ClassII, DivisionI & II, Group E,F,G ClassIII Temp.Code: T5/T4 Other:IP66 IK10	T5(-40°C to +40°C) T4(-40°C to +55°C)
XF Linear Light Class I, Division II		XF-4-6-C-D-Z-WM 4FT	60W	Sold Out 90pcs ETA to WH 9/5 Dimmable	8400lm	5000K	120°	Marine:UL 1598A,ABS UL 844: Class I, DivisionII, GroupA,B,C,D ClassII, DivisionI & II, Group E,F,G ClassIII Temp.Code: T5/T4 Other:IP66 IK10	T5(-40°C to +40°C) T4(-40°C to +55°C)
XF Linear Light Class I, Division II		XF-4-8-C-D-Z-WM 4FT	80W	Sold Out 100pcs ETA to WH 9/15 Dimmable	10800lm	5000K	120°	Marine:UL 1598A,ABS UL 844: Class I, DivisionII, GroupA,B,C,D ClassII, DivisionI & II, Group E,F,G ClassIII Temp.Code: T5/T4 Other:IP66 IK10	T5(-40°C to +40°C) T4(-40°C to +55°C)
LFL Series, Flood/Area Light Class I, Division II		LFL-1-E-LV1-C-Z-TM	200W	170pcs	2600lm	5000K	120°	Marine:UL 1598A,ABS UL 844: Class I, DivisionII, GroupA,B,C,D ClassII, DivisionI & II, Group E,F,G ClassIII	- 104°F to 131°F (-40°C to +55°C)
LFL Series, Flood/Area Light Class I, Division II		LFL-2-D-LV1-C-Z-TM	150W	20pcs	19500lm	5000K	120°	Temp.Code: T4(LFL2),T3(LFL1) Other:IP66 IK10	- 104°F to 131°F (-40°C to +55°C)
LFL Series, Flood/Area Light Class I, Division II		LFL-2-C-LV1-C-Z-TM	100W	Sold Out	13500lm	5000K	120°	Temp.Code: T4(LFL2),T3(LFL1) Other:IP66 IK10	- 104°F to 131°F (-40°C to +55°C)
ZTP Series Exit Light Class I, Division I		ZTP-5-RD-LV Double-Faced with Red letters & White Panel	5W	60pcs	650lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C
LUMIX-G Series (LGE) Exit Light Class I, Division II		LGE-5-LV-G-WM Green Leds	5W	Sold Out	300lm	5000K	120°	Marine:UL 1598A,ABS UL 844: Class I, DivisionII, GroupA,B,C,D ClassII, DivisionI & II, Group E,F,G ClassIII Temp.Code: T5/T4 Other:IP66 IK10	Ta= 0°C to + 45°C, when batteryis charged; Ta= -10°C to + 60°C, when battery discharges

TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

Inventory Levels as of Aug. 6, 2025

FME LIGHTING | 877-234-8460 | info@fmelighting.com

REP PRICING FIRM UNTIL: Q3 2025

*Accessories 13 to 23 are compatible with all series with the exception of the LIH, NEB, SOL & ROC.

ACCESSORIES

Picture	Model	Stock Available	Description
	SOL-CM	Sold Out	Ceiling Mount Bracket for Solstice Series 4x 3/4"NPT Cable Entries, 3 sealed by blanking plugs
	SOL-WM	43pcs	Wall Mount Bracket for Solstice Series 4x 3/4"NPT Cable Entries, 3 sealed by blanking plugs
	NEB-CM	24pcs	Ceiling Mount Bracket for Nebula Series 4x 3/4"NPT Cable Entries, 3 sealed by blanking plugs
	NEB-WM	51pcs	Wall Mount Bracket for Nebula Series 4x 3/4"NPT Cable Entries, 3 sealed by blanking plugs
	ROC-PLM	50pcs	Rocket Series Pole Adaptor
	1- Meter Safety Chain	140pcs	1- Meter Safety Chain
	Slip Fitter	90pcs 100pcs ETA to WH 9/20	Slip Fitter
	OPEB	290pcs	JUNCTION BOX C1,D1
	FME-MID-PM	90 sets	Mounting Pole & Clamp for Meridian (MID) Series fixtures
	OPWA25	200pcs	C1, D1 25 DEGREE WALL MOUNT
	OPWA90	30pcs	C1, D1 90 DEGREE WALL MOUNT & JUNCTION Box
	OPPS25	Sold Out	25 DEGREE POLE MOUNT
	OPPS90	30pcs 120pcs ETA to WH 9/5	90 DEGREE POLE MOUNT
	OPWA	180pcs	90 DEGREE WALL MOUNT

TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

Inventory Levels as of Aug. 6, 2025
FME LIGHTING | 877-234-8460 | info@fmelighting.com
REP PRICING FIRM UNTIL: Q3 2025
**Accessories 13 to 23 are compatible with all series with the exception of the LIH, NEB, SOL & ROC.*

ACCESSORIES

Picture	Model	Stock Available	Description
	NIP-3/4	300pcs	3/4" THREADED CONDUIT NIPPLE
	HOOK-1	50pcs	3/4" HOOK